

DIGITUS Hirose Modular Plug, CAT 6 TM 21 - 10 pieces

A-MO6-8-8-HRS-10
EAN 4016032494959



Hirose Modular Plug, CAT 6 TM21 8P8C, shielded, for round cable, incl. hood, 10 pcs

These modular plugs can be used to establish quick and simple connections.

- Easy assembly by modular crimping tool DN-94008
- Layout performance: CAT 6, 1GBase-T
- Area of application: Patch cable assembly
- General properties:
- Fully shielded with strain relief for installation cables
- Incl. comb
- Technical properties:

- Mating cycles: ≥ 750 (ISO/IEC 11801, IEC 60603-7-5)
- Material connector body: Polycarbonat, clear
- Connector contact: Phosphor bronze, brass 0.8μ gold-plated
- Material shielding housing: Brass 0.5 mm, 2μ nickel-plated
- Flammability: UL 94V-2
- Physical properties:
- Insertion force: 30N max. (IEC 60603-7-5)
- Diameter Cu-Conductor: AWG (27/7 ... 24/7)
- Operating temperature: -20°C to $+60^{\circ}\text{C}$
- Current carrying capacity: 1A at 50°C
- Diameter outer jacket: 5,5 ... 6,2mm
- 10 pieces

Logistics

	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm ³
Packaging Unit Carton	10	0.85	21.00	22.00	10.00	4,620.00
Packaging Unit Inside	1	0.09	12.00	10.00	3.50	420.00
Packaging Unit Single	1	0.09	12.00	10.00	3.50	420.00
Net single without Packaging	1	0.00	0.00	0.00	0.00	0.00