

Note:

1.RoHS 3.0 & Reach Compliant

2.Text:

Test Grade Designation:Each to Reference		
Grade IL/RL	Standard	
Insertion Loss (IL)	≤0.3dB	IEC 61300-3-4
Return Loss(RL)	≥30dB	IEC 61300-3-6
Test Wavelength	850nm	
End face inspection	×400	

3.Operating Temperature:-40° C ~+85° C

4.Storage Temperature:-20° C ~+70° C

5.Min. bending radius : 10*D(Static) 20*D(Dynamic)
D:diameter of cable

MATERIAL LIST:

⑧	Ring 1 2	4pcs	
⑦	Black Heat Shrink Tube	2pcs	
⑥	LC Clip Erika violet RAL4003	2pcs	
⑤	LC Dust Cap White	4pcs	
④	LC Duplex Connector Erika violet RAL4003	4pcs	
③	Flex-Angle boot ID: 2.0mm	4pcs	
②	LC/UPC MM Ferrule 126-128um	4pcs	
①	Fiber Optical Cable Duplex Ø2.0mm OM4 50/125um Erika violet RAL4003 LSZH	L+0.1m	
NO.	SPECIFICATION STANDARD	QT' Y	REMARK

					SYNERGY 21				
					CUSTOMER		ITEM NO.		
		change "ROSH 2.0" to "ROSH 3.0"	2022-02-25	A1	PRODUCT NAME	LC/UPC-LC/UPC DX OM4 2.0mm, Flex-Angle boot	UNO ITEM NO.	115991	UNIT MM
		NEW	2021-11-09	A0	DRAWNBY	CHECKBY	APPOBY	DATE	
BY	CHK	REVISION RECORD MODIFICATIONS	DATE	REV.	SYNERGY 21	SYNERGY 21	SYNERGY 21	2021-11-09	

TEST REPORT					
Batch No.		Attention: Please clean the fiber surface! Achtung: Bitte reinigen Sie Steckanschl�flichkeit 			
Artikel NO.					
ITEM Number					
Description					
Notes					
Min.bending radius (mm)	Static: 10*D	D: Cable diameter			
	Dynamic: 20*D				
TEST VALUES					
Standard (Each to Reference)	Allow Loss	CHANNEL 1		CHANNEL 2	
	$\lambda=1310nm$	Conn. 1	Conn. 2	Conn. 1	Conn. 2
Insertion Loss (IEC 61300-3-4)	$\leq 0.30dB$	dB	dB	dB	dB
Return Loss (IEC 61300-3-6)	UPC $\geq 50dB$	dB	dB	dB	dB
	APC $\geq 60dB$				
RESULT		OK			

PACKING DRAW




Chart:

Item No.	Package	EAN Code	LENGTH(MM)
S217020	SinglePack: 1pc/SYNERGY 21 A bag/test report+label; SubPack: no; Carton +labelx2;	4038816113559	500
S217021	SinglePack: 1pc/SYNERGY 21 A bag/test report+label; SubPack: no; Carton +labelx2;	4038816207227	1000
S217022	SinglePack: 1pc/SYNERGY 21 A bag/test report+label; SubPack: no; Carton +labelx2;	4038816113580	1500
S217023	SinglePack: 1pc/SYNERGY 21 A bag/test report+label; SubPack: no; Carton +labelx2;	4038816113757	2000
S217024	SinglePack: 1pc/SYNERGY 21 A bag/test report+label; SubPack: no; Carton +labelx2;	4038816113795	3000
S217025	SinglePack: 1pc/SYNERGY 21 B bag/test report+label; SubPack: no; Carton +labelx2;	4038816113818	5000
S217026	SinglePack: 1pc/SYNERGY 21 B bag/test report+label; SubPack: no; Carton +labelx2;	4038816113825	7500
S217027	SinglePack: 1pc/SYNERGY 21 A bag/test report+label; SubPack: no; Carton +labelx2;	4038816113832	10000
S217028	SinglePack: 1pc/SYNERGY 21 C bag/test report+label; SubPack: no; Carton +labelx2;	4038816113887	15000
S217029	SinglePack: 1pc/SYNERGY 21 C bag/test report+label; SubPack: no; Carton +labelx2;	4038816113900	20000

						SYNERGY 21						
						CUSTOMER				ITEM NO.	see the chart	
						PRODUCT NAME	LC/UPC-LC/UPC DX OM4 2.0mm, Flex-Angle boot		Manufacture country	CHINA	UNIT	MM
		NEW	2021-11-08	A		DRAWNBY	CHECKBY	APPOBY	DATE			
BY	CHK	REVISION RECORD MODIFICATIONS	DATE	REV		SYNERGY 21	SYNERGY 21	SYNERGY 21	2021-11-08			