

Delock Extension Socket Cube 3-way with childproof lock and USB PD 3.0 charger 20 W, 1.5 m cable, white

Description

The extension socket cube by Delock with USB charging function is suitable for convenient connection of various devices. A wall bracket is integrated, so that the socket can also be mounted on the wall or under the desk.



Make 3 out of 1

Whether in the kitchen, living area or office. There is a lack of free sockets. This multiple socket makes three out of one free grounded socket. The cube shape also provides a space-saving solution.

Item no. 11502

EAN: 4043619115020

Country of origin: China

Package: Retail Box

USB charger included

In addition to the sockets, one USB Type-C™ and one USB Type-A charging ports are provided. Common fast charging technologies, such as Power Delivery (PD) 3.0, are supported. This makes the charging process as safe and fast as possible.

Specification

- Connectors:
 - Input:
 - 1 x plug CEE 7/7
 - Output:
 - 3 x socket CEE 7/3
 - 1 x USB Type-A female
 - 1 x USB Type-C™ female
- Rated current: 16.0 A / 250 V~
- Rated power: 3680.0 W
- Wall-mount option
- LEDs for status monitoring
- USB Charger:
 - Input: AC 250 V / 50 Hz / 0.5 A
 - Output power: max. 20.0 W total
 - USB-A: 5.0 V / 3.0 A, 9.0 V / 2.22 A, 12.0 V / 1.67 A

USB-C™: 5.0 V / 3.0 A, 9.0 V / 2.22 A, 12.0 V / 1.67 A

Over current protection, over heating protection, short circuit protection

- Average active efficiency 82.06 %
- Efficiency at low load (10 %) 78.21 %
- No-load power consumption 0.138 W
- Colour: white
- Cable length: ca. 1.5 m
- Dimensions (LxWxH): ca. 62 x 62 x 65 mm

Package content

- Socket cube
- 2 screws
- User manual

Images



General

Protection:	Input overvoltage protection Short circuit protection Overheating protection
-------------	--

Interface

Connector 1:	1 x plug CEE 7/7
Connector 2:	3 x Steckdose CEE 7/3 mit Kindersicherung
connector 3:	1 x USB Type-C™ Power Delivery female 1 x USB Type-A female

Physical characteristics

Length:	66 mm
Width:	66 mm
Height:	87 mm
Colour:	white

Power supply

Input:	AC 100 - 240 V / 50 - 60 Hz / 0.5 A
Output:	5.0 V / 3.0 A 12,0 V / 1,67 A 9,0 V / 2,22 A