



Delock HDMI Audio Extractor 4K 60 Hz compact

Description

This adapter by Delock can be used to **extract the audio signal** from an HDMI transmission. While the video signal is displayed on a TV or monitor, the audio signal can be sent **digital (S/PDIF) or analogue (stereo)** to other devices, such as **headphones or a surround receiver**.

Small and practical

The device can be connected directly to the monitor or the TV, the short cable fits easily into side or recessed HDMI ports. The source, e.g. a **TV streaming stick**, can be connected to the **input port**.



Specification

- Connectors:
 - Input:
 - 1 x HDMI-A female
 - 1 x USB Type Micro-B female (5 V power supply)
 - Output:
 - 1 x HDMI-A male
 - 1 x 3.5 mm 3 pin stereo jack female (audio)
 - 1 x TOSLINK female S/PDIF
- High Speed HDMI, 3D and HDCP 1.4 / HDCP 2.2
- Supports HDR (High Dynamic Range)
- Automatic switching to stereo (2.0) when using the stereo jack and automatic muting of the digital output
- Resolution up to 3840 x 2160 @ 60 Hz
- Video bandwidth up to 600 MHz / 6 Gbps, max. 18 Gbps
- Supports all common 2.0 and 5.1 audio formats: LPCM, Dolby Digital, DTS Audio
- Supported sample rates: 16 / 20 / 24 bit, 32 / 44.1 / 48 / 88.2 / 96 kHz (depending on the system and the connected devices)
- CEC and HDMI audio routed to the output (pass-through)
- Power supply via USB (power supply not included)
- Power consumption: max. 2 W
- Colour: black
- Cable length without connectors: ca. 12.5 cm
- Dimensions without cable (LxWxH): ca. 58 x 58 x 16 mm

System requirements

- A free HDMI-A female
- Power source with a free USB Type-A female port

Package content

- HDMI Audio Extractor
- USB Type-A to Type Micro-B cable, length ca. 30 cm
- User manual

Item no. 63333


EAN: 4043619633333

Country of origin: China

Package: • Retail Box



Images





General

Specification:	DTS Audio
	High Speed HDMI
	Dolby Digital
	HDCP 1.4
	HDCP 2.2
	LPCM
	HDR

Interface

Output:	1 x HDMI-A 19 pin male
	1 x 3.5 mm 3 pin stereo jack female
	1 x TOSLINK female
Input:	1 x HDMI-A 19 pin female
	1 x USB 2.0 type Micro-B female

Technical characteristics

Maximum screen resolution:	3840 x 2160 @ 60 Hz
Video bandwidth:	600 MHz / 6 Gbps

Physical characteristics

Housing colour:	black
Housing material:	Plastic