

# Delock Adapter USB Type-C™ male to DisplayPort female (DP Alt Mode) 4K 60 Hz

## Description

This adapter by Delock is suitable for the connection of a **DisplayPort monitor** to a computer with USB-C™ interface and DisplayPort alternate mode support. Thus, the adapter can be connected to different laptops like MacBook, Chromebook and similar. In addition, the adapter can also be operated on a Thunderbolt™ 3 interface.



**Item no. 64151**

EAN: 4043619641512

Country of origin: China

Package: Zip poly bag

## Technical details

- Connectors:
  - 1 x USB Type-C™ male >
  - 1 x DisplayPort female
- Chipset: Fresco Logic FL7102
- Resolution up to 3840 x 2160 @ 60 Hz  
(depending on the system and the connected hardware)
- Transmission of audio and video signals
- Supports HDCP
- Supports HDR
- USB bus powered
- Plug & Play
- Dimensions incl. connector (LxWxH): ca. 48.6 x 22.5 x 10.3 mm
- Colour: black

## System requirements

- Android 10.0 or above

- Chrome OS 87.0 or above
- iPad Pro (3rd Generation) or above
- Linux Kernel 5.4 or above
- Mac OS 11.0.1 or above
- Windows 8.1/8.1-64/10/10-64
- PC or laptop with a free USB Type-C™ port and DisplayPort alternate mode or
- PC or laptop with a free Thunderbolt™ 3 port

---

## Package content

- USB-C™ to DisplayPort adapter

## General

|                             |                                                                                                                                                                                                                                     |
|-----------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Function:                   | Plug & Play                                                                                                                                                                                                                         |
| Supported operating system: | Linux Kernel 5.4 or above<br>Mac OS 11.0.1 or above<br>Windows 10 32-Bit<br>Windows 10 64-Bit<br>Windows 8.1 32-Bit<br>Windows 8.1 64-Bit<br>Android 10.0 or above<br>iPad Pro (3rd Generation) or above<br>Chrome OS 87.0 or above |

## Interface

|         |                        |
|---------|------------------------|
| Output: | 1 x DisplayPort female |
| Input:  | 1 x USB Type-C™ male   |

## Technical characteristics

|                            |                     |
|----------------------------|---------------------|
| Chipset:                   | Fresco Logic FL7102 |
| Maximum screen resolution: | 3840 x 2160 @ 60 Hz |
| Signal transmission:       | video<br>audio      |
| Voltage:                   | USB bus powered     |

## Physical characteristics

|         |         |
|---------|---------|
| Length: | 48.6 mm |
| Width:  | 22.5 mm |
| Height: | 10.3 mm |
| Colour: | black   |