

# Delock PoweredUSB cable male 12 V to DC 5.5 x 2.5 mm male angled 2 m

## Description

This PoweredUSB cable by Delock can be used to supply power to a device with DC 5.5 x 2.1 mm female port via a PC or hub with PoweredUSB 12 V port.



**Item no. 80610**

EAN: 4043619806102

Country of origin: China

Package: Zip poly bag

## Specification

- Connectors:
  - 1 x PoweredUSB male 12 V
  - 1 x DC 5.5 x 2.5 mm male angled
- PoweredUSB specification
- Voltage: 12 V
- Cable gauge: 20 AWG
- Cable diameter: ca. 4.2 mm
- Cable double shielded
- Cable jacket material: PVC
- Colour: black
- Length incl. connectors: ca. 2 m

## Package content

- PoweredUSB cable

## Images



PoweredUSB  
12 V



DC 5,5 x 2,5 mm

## General

|                |            |
|----------------|------------|
| Specification: | PoweredUSB |
|----------------|------------|

## Interface

|              |                          |
|--------------|--------------------------|
| Connector 1: | 1 x PoweredUSB male 12 V |
| Connector 2: | 1 x DC 5.5 x 2.5 mm male |

## Technical characteristics

|          |      |
|----------|------|
| Voltage: | 12 V |
|----------|------|

## Physical characteristics

|                        |        |
|------------------------|--------|
| Conductor gauge:       | 20 AWG |
| Shielding:             | double |
| Length:                | 2 m    |
| Colour:                | black  |
| Cable diameter:        | 4.2 mm |
| Cable jacket material: | PVC    |