



Delock Cable SATA 6 Gb/s 7 pin receptacle + Floppy 4 pin power receptacle (5 V + 12 V) > SATA 22 pin receptacle straight 30 cm

Description

This cable by Delock enables the connection of a device with 22 pin SATA interface over a free SATA port and a free 4 pin Floppy power interface of the motherboard.



Specification

- Connector:
SATA 6 Gb/s 7 pin receptacle upwards angled + Floppy 4 pin power receptacle > SATA 6 Gb/s 22 pin (7 pin data + 15 pin power) receptacle straight
- Compatible to motherboards of the Fujitsu D3003/3313 series and Gigabyte GA-H110TN Mini-ITX series
- Data transfer rate up to 6 Gb/s
- Downwards compatible to SATA 1.5 Gb/s and 3 Gb/s
- Version with 4 power wires (yellow = 12 V, black = GND, red = 5 V)
- Voltage: 5 V + 12 V
- Cable gauge:
30 AWG data line
22 AWG power line
- Length without connector: ca. 30 cm

System requirements

- A free SATA interface
- A free Floppy power plug

Package content

- SATA cable

Item No. 84852

EAN: 4043619848522

Country of origin: China

Package: Poly bag



Images





General	
Specification:	SATA 6 Gb/s
Interface	
Connection 1:	1 x SATA 6 Gb/s 22 pin receptacle
Connection 2:	1 x SATA 6 Gb/s 7 pin female
	1 x Floppy 4 pin power female
Technical characteristics	
Data transfer rate:	6 Gb/s
Voltage:	5 V
	12 V
Physical characteristics	
Conductor gauge:	30 AWG data line
	22 AWG power line
Length:	30 cm