



Delock USB Docking Station Dual HDMI Full-HD / USB 3.2 / LAN / Audio

Description

This docking station by Delock can be connected to a computer with a USB-C™ or USB Type-A port and provides a variety of interfaces. Two monitors can be operated simultaneously at the HDMI output ports. Four built-in USB 2.0 ports and two USB 3.2 Gen 1 ports allow the use of peripherals, and connections for microphone and speaker and Gigabit network complete the features.

Full-HD resolution

Full-HD (1080p) resolution is possible when using only one monitor and also when using both HDMI outputs at the same time.



Specification

- Connectors:
front side:
1 x SuperSpeed USB (USB 3.2 Gen 1) Type-A female
1 x SuperSpeed USB (USB 3.2 Gen 1) Type-A female - Battery Charging specification BC1.2
1 x microphone 3.5 mm stereo jack
1 x speaker 3.5 mm stereo jack
back side:
1 x SuperSpeed USB (USB 3.2 Gen 1) Type-B female
1 x DC 5 V power connector
2 x HDMI-A female
1 x Gigabit LAN 10/100/1000 Mbps RJ45 jack
4 x USB 2.0 Type-A female
- Maximum resolution (depending on the system and the connected hardware):
Single display: up to 2560 x 1440 @ 50 Hz
Dual display: up to 2048 x 1152 @ 60 Hz
- Transmission of audio and video signals
- Functions: Mirrored or Extended (under Windows only one display can be mirrored, the second one is extended)
- Colour: black / white
- Dimensions without stand (LxWxH): ca. 190 x 78 x 38 mm

Power supply specification

- Wall power supply
- Input: AC 100 ~ 240 V / 50 ~ 60 Hz / 0.8 A
- Output: 5 V / 4 A
- Ground outside, plus inside
- Dimensions:
inside: ø ca. 1.7 mm
outside: ø ca. 4.75 mm
length: ca. 9.5 mm

System requirements

- Mac OS 10.15.5 or above
- Windows 8.1/8.1-64/10/10-64
- PC or laptop with a free USB Type-A port or
- PC or laptop with a free USB Type-C™ port

Package content

Item no. 87771

EAN: 4043619877713

Country of origin: China

Package: • Retail Box



- USB docking station
- Cable USB Type-B male to USB Type-A male (with adapter to USB Type-C™ male), length ca. 1 m
- Power supply
- User manual

Images





General

Function:	mirror and extend
Supported operating system:	Windows 8.1 32-bit
	Windows 8.1 64-bit
	Windows 10 32-bit
	Windows 10 64-bit
	Mac OS 10.15.5 or above

Technical characteristics

Maximum screen resolution:	2048 x 1152 @ 60 Hz
	2560 x 1440 @ 50 Hz