

InLine® Patch Cable S/FTP PiMF Cat.6A halogen free 500MHz black 20m



* Preise inkl. gesetzlicher MwSt. zzgl. Versandkosten

Marke: INL

Bestell-Nr.: 76820S

LINKWARE			
Cable ID: UNOSSRD02032020-29			
Test Summary: PASS			
DATE: 06/23/2008 11:35am	Operator: DC	Model: DTK1800	
HeadNode: 2.6 dB	Software Version: 2.32	Main SW: 0225032	
Test Link: TM Cat 6A Channel	Link Version: 1.37	Reverse SW: 0225031	
Cable Type: Cat7 SFTP	MVP: 10%	Main Adapter: DTK-CHAN01	
Fault Anomaly Threshold: 15%		Remote Adapter: DTK-CHAN01	



Patch cable in the highest quality for a professional cabling in Gigabit and 10 Gigabit range, for use in data centers and server racks

- Assignment according to TIA/EIA 568B2.1
- cable construction S/FTP (PiMf) 4x2xAWG26/7
- overall braided shield with paired foil shield
- Cable sheath halogen free, LSZH, conform to standards IEC 60332-1-2, IEC 60754-1, IEC 60754-2, IEC 61034 IEC332-1
- plug RJ45 (8P8C) with 50µ" gold plated contacts and with special design and latch protection
- blue colored plug for easy distinction
- For Gigabit and 10 Gigabit applications
- to 500MHz: 100% Cat.6 test and 100% Cat.6A test (Fluke Channel Link Test) including the attached test protocol and serial number
- in reclosable PE bag with EAN code

Artikeleigenschaften

Länge: 20m
Farbe: schwarz