



Argus ST-7266 – Your RJ45 adapter for the 2.5 Gigabit network

The built-in Realtek® chipset RTL8125B offers excellent performance and ensures fast data throughput. In addition, the main processor is further relieved by the ST-7266, so that the network transfer no longer puts as much strain on the main processor, which is often the case when using normal network cards in a server environment. The connection is made through an RJ45 port with a speed of up to 2.5G.

- ✓ Single RJ45 adapter
- ✓ for the 2.5 Gigabit network
- ✓ Realtek® chipset RTL8125B
- ✓ supports WOL (Wake-On-LAN)

Specifications

Interface	PCIe x1 v2.1
Connectors	1x RJ45 100M/1G/2.5G
Chipset	Realtek® RTL8125B
Operating System	Windows 7/8/8.1/10/11/Server 2012/Linux
Dimensions (H/W/D)	22x120x85mm
Package Dimensions (H/W/D)	28x180x150mm
Weight (net)	35g
Weight (gross)	130g
Packing Units (VE/VPE/PAL)	1/50
Warranty	12 Months
Article Number	77773013
EAN-Code	4260455647878
Scope of Delivery	Driver CD Low-profile slot bracket
Features	Hardware ECC (Error Correction Code) Hardware CRC (Cyclic Redundancy Check) PCI MSI (Message Signal Interrupt) and MSI-X Supports ECMA-393 ProxZzzy standard Wake-On-LAN and "RealWow!" technology IEEE1588v1, IEEE1588v2, IEEE80.2AS Zeit-Sync IEEE802.1P layer 2 priority coding IEEE802.1Q VLAN tag IEEE802.3az-2010 IEEE802.3bz-2016 (NGBASET) Full Duplex Flow Control (IEEE802.3x) Jumbo Frames up to 16KB Virtual Machine Queue (VMQ) Quad-Core Receive-Side Zoom (RSS)