

CITIZEN

High speed POS printing with front exit

Hospitality highest standard

Customisable LCD display

With the ability to add company logos and scrolling messages, the POS printing experience can be personalised to any business' requirements. Printer managers can programme the printer to display specific messages to make everyday operation even easier – low paper warnings, error messages and even instructions on how to order more receipt rolls – whatever the user deems relevant to their printing processes.

In a hurry?

With 500mm/sec. print speed the CT-S851III is the fastest POS printer in the market.



CT-S851III

POS, Receipt printer (thermal 3 inch / 80mm)

Applications

- Hospitality
- Kiosk
- Kitchen
- Retail



Usability, reliability and outstanding performance

TOMORROW'S PRINTING TODAY

Specifications

Model	CT-S851III
Printing Technology	Direct Thermal
Resolution	203 dpi
Print Speed (maximum)	500mm/sec
Print Width (maximum)	80 mm
Media Width (min to max)	58 / 60 / 80 / 83 mm (+/- 1 mm)
Roll Size (max), Core Size	83 mm outside diameter
Media Thickness (min to max)	65 to 75 µm or 75 to 85 µm
Main Interface	USB 2.0 full speed
Optional interfaces	Bluetooth with Apple™ MFi compatibility, Powered USB, USB with hub, Serial (RS-232C compliant), Parallel (IEEE 1284 compliant), Ethernet + USB host
Power supply	100 - 240V, 50/60hz
Reliability	200 Million pulses or 150 Km, 2 million cuts
Emulations (Languages)	ESC/POS™
Drivers and software	Free-of-charge from website, including support for various platforms
Size (W x D x H) and Weight	145x192x142 mm, 1.9Kg (DC version: 145x192x114 mm, 1.5kg)
Cutter	Guillotine type, full and partial
EMC and safety standards	CE, TUV, UL, C-UL, FCC class A

All product names are trademarks of the respective manufacturers. Zebra®, ZPL and EPL are trademarks of ZIH Corp. Datamax® is a trademark of Datamax-O'Neil Corporation. Designs, specifications and availability are subject to change without notice. Errors and omissions excluded. © Citizen Systems Europe GmbH, V.1.0

CT-S851III

POS, Receipt printer (thermal 3 inch / 80mm)

Features & Benefits

- Paper exit: Front exit - prevents damage from moisture or foreign objects
- Paper load: Easy paper loading
- Printing Speed: Ultra fast print out - up to 500mm per second
- Display: LCD display for easy configuration and operation
- Low space requirement - integrated power supply enables clean work station
- Mobile-POS ready
- Easy notification - built-in buzzer
- ENERGY STAR® compliant
- Small footprint
- Recyclable packacking
- Tool-free maintenance