

DS-KAW150-4N **Power Supply**



- Short circuit protection, over load protection, and over power voltage protection
- Natural air cooling
- LED power indicator
- 105 °C long life electrolytic capacitor
- 5 seconds 300 VAC surge voltage input tolerance

▪ Specification

General	
Working temperature	Operating: -10 °C to +70 °C (14 °F to 158 °F) Storage: -25 °C to +85 °C (-13 °F to 185 °F)
Working humidity	< 95% (no condensation)
Input voltage	100 VAC to 240 VAC
Output voltage	48 VDC
Output current	3.2 A
Output power	150 W
Noise and ripple	< 150 mVpp @ 25 °C
Voltage adjustment range	23 VDC to 25 VDC
Cooling system	Convection
Dimension (L x W x D)	178 mm × 97 mm × 38 mm (7.01" × 3.82" × 1.50")
Weight	0.54 kg

▪ Available Model

DS-KAW150-4N

Headquarters

No.555 Qianmo Road, Binjiang District,
Hangzhou 310051, China
T +86-571-8807-5998
www.hikvision.com



Follow us on social media to get the latest product and solution information.



Hikvision



HikvisionHQ



HikvisionHQ



Hikvision_Global



Hikvision
Corporate Channel



hikvisionhq