




8-Port Gigabit L2 Managed PoE+ Switch with 2 SFP Slots

Model: **GS** 2008PS2



Features

- 8 x 10/100/1000Mbps auto-sensing PoE Ports, 2 x Gigabit SFP Uplink Ports, 1 x Console Port
- Support IEEE802.3/IEEE802.3i/IEEE802.3u/IEEE802.3ab/IEEE802.3z
- Compatible with IEEE802.3at (30W) and IEEE802.3af (15.4w)
- Ethernet port supports 10/100/1000M adaptive
- Panel indicator monitoring the status and help failure analysis
- Fanless design, Natural Cooling,Compatible with 1U Rack Mount
- Support 802.1x port authentication, support AAA authentication, support TACACS+ authentication
- Support WEB, TELNET, CLI, SSH, SNMP, RMON management
- Support PoE Power Management, PoE watch dog
- Lightning Protection Surge: General Mode 6KV, Differential Mode 4KV, ESD 15KV

Specifications

Model	GS2008PS2
AC INPUT	AC100-240V, 50/60Hz
Ethernet Port	8 * 10/100/1000Mbps PoE Port
	2* 1000Mbps SFP Port
	1 * RJ45 Console Port
Bandwidth	20Gbps
Packet Forwarding rate	14.88Mpps
DDR SDRAM	128MB
Flash Memory	16MB
Packet Buffer Memory	4M
MAC Address	8K
Jumbo frame	9.6Kbytes
VLANs	4096



Standard

Network Protocols	IEEE 802.3: Ethernet MAC Protocol
	IEEE 802.3i: 10BASE-T Ethernet
	IEEE 802.3u: 100BASE-TX Fast Ethernet
	IEEE 802.3ab: 1000BASE-T Gigabit Ethernet
	IEEE 802.3z: 1000BASE-X Gigabit Ethernet (optical fiber)
	IEEE 802.3ad: Standard method for performing link aggregation
	IEEE 802.3x: Flow control
	IEEE 802.1ab: LLDP/LLDP-MED (Link Layer Discovery Protocol)
	IEEE 802.1p: LAN Layer QoS/CoS Protocol Traffic Prioritization
	(Multicast filtering function)
	IEEE 802.1q: VLAN Bridge Operation
	IEEE 802.1x: Client/Server Access Control and
	Authentication Protocol
	IEEE 802.1d: STP
	IEEE 802.1s: MSTP
	IEEE 802.1w: RSTP
PoE protocol	IEEE802.3af (15.4 W)
	IEEE802.3at (30 W)

Industry Standard	EMI: FCC Part 15 CISPR (EN55032) class A
	EMS: EN61000-4-2 (ESD)、 EN61000-4-4 (EFT)、
	EN61000-4-5 (Surge)
	Shock: IEC 60068-2-27
	Free Fall: IEC 60068-2-32
	Vibration: IEC 60068-2-6
Network Media	10BASE-T: Cat3、 4、 5 or above UTP(≤100 M)
	100BASE-TX: Cat5 or above UTP(≤100 M)
	1000BASE-TX: Cat5 or above UTP(≤100 M)
Fiber Medium	Multi-mode Fiber: 50/125、 62.5/125、 100/140um
	Single-mode Fiber: 8/125、 8.7/125、 9/125、 10/125um

Environmental standards

Working Environment	Operating temperature: -20~50°C
	Storage temperature: -40~85°C
	Operating Humidity: 10%~90%, No condensation
	Storage Humidity: 5%~90%, No condensation
	Working height: Up to 10,000 feet
	Storage height: Up to 10,000 feet



Function indication

Indicator	PWR, SYS, SW, PoE, Link/ACT
PWR (Power Indicator)	Lighting: Powered
	Un-Light: No Power
SYS (System Indicator)	Flashing: System Start-up
	Lighting: System Running
Mode (DIP Indicator)	Lighting: VLAN
	Un-Light: Default
	Flashing: Extend
PoE	Lighting: PoE on
	Un-Light: PoE off
Link/ACT	Lighting: Link connection
	Flashing: Data transmission
	Un-Light: Link disconnect

DIP Function	VLAN、 Default、 Extend、 Reset
VLAN	1-8 ports are isolated from each other, and the PoE Watchdog function is open (hardware takes precedence over software)
Default	All ports can communicate with each other, PoE Watchdog is closed
Extend	7-8 Port: Supports 250m link extension at a rate of 10M, other ports normal, PoE Watchdog open (hardware takes precedence over software)
Reset	Short press restart, long press 5 seconds to restore factory Settings



Physical specifications

Product Information	Product Dimensions: 268*181*44mm
	Package Dimensions: 312*260*84mm
	Product N.W: 1.2KG
	Product G.W: 1.7KG
Packing Information	Carton Dimensions: 540*435*332mm
	Packing Qantity: 10PCS
	Packing weight: 18KG
Voltage	Input Voltage: AC100-240V/50-60Hz
	Power supply: 52V2.3A
Packing list	1. Ethernet switch: 1 Set
	2. Instruction manual: 1 PCS
	3. Certificate: 1 PCS
	4. Power cord: 1PCS
	5. Serial cable: 1PCS
	6. Operation manual CD: 1 PCS
	7. Brackets: 1 pair

Software function

Basic function	Support hardware watchdog, factory reset, system and port LED
	Support global information, statistical information, log information
	Support User management, alarm management, configuration management
	Support Port rate, duplex, flow control, maximum frame length configuration
PoE function	Support Port mirroring, port speed limit, port energy saving
	Support PoE time management
	Support PoE automatic monitoring / PoE Watchdog
VLAN	Support PoE port power configuration
	Support 4K VLAN
	Support 802.1Q VLAN, baesd on port VLAN
	SupportAccess、 Trunk、 Hybrid VLAN mode
	Support GVRP (VLAN registration protocol)
	Support MAC VLAN 、 IP VLAN
MAC	Support Voice VLAN
	Support MAC address automatic learning and aging
	Support Static, dynamic, filtered address table



Security features	Password protection
	Support Restrict user access based on port number, IP address, MAC address
	Support HTTPS、SSH V1/V2
	Support VLAN-IP-MAC-PORT binding
	Support ARP detection, IP source protection, DoS protection
	Support DHCP Snooping、DHCP Attack protection
	Support 802.1X Certification
	SupportAAA (Authentication, Authorization, Accounting),
	Support RADIUS protocal
	Support Port security, port isolation
Access control	Support L2(Layer 2)~L4(Layer 4) Packet filtering function
	Support Port mirroring, flow rate limiting, QoS remarking
QOS	Support 8 port queues
	Support Port priority, 802.1P priority, DSCP priority
	Support SP, WRR Priority scheduling algorithm
Spanning tree	Support STP(IEEE 802.1d), RSTP(IEEE 802.1w) and MSTP (IEEE 802.1s) protocal
	Support Multi-instance, Support Aggregate interface
	Support BPDU protection

Multicast	Support IGMP v1/v2/v3 Snooping
	Support MLD v1/v2 Snooping
	Support Layer 2 multicast fast leave mechanism, querier
	Support Layer 2 IPv4 static multicast
	Support Layer 2 IPv6 static multicast
	Support IGMP v1/v2/v3 Layer 3 multicast
Storm suppression	Support multicast suppression
	Support broadcast storm suppression
	Support unknown unicast suppression
Ring protection	Support Ring protection
Link Aggregation	Support Static Aggregation
	Support LACP Dynamic Aggregation
	Support based on IP, MAC, mixed load-balancing modes
	Maximum support 8 aggregation groups (8 ports per aggregation group)
IPv6	Support IPv6 Ping、IPv6 Traceroute、IPv6 Telnet
	Support IPv6 SSH
	Support IPv6 HTTP 、IPv6 HTTPS



Management and Maintenance	Support WEB Management (HTTP、 HTTPS)
	Support CLI (Telnet, SSH V1/V2, Local serial port)
	Support SNMP V1/V2/V3
	Support RMON V2
	Support LLDP Device discovery
	Support SNTP Time synchronization
	Support CPU Monitoring, Memory Monitoring
	Support System log, classification warning
	Support Ping, Traceroute detection, cable detection
	Support WEB Management (HTTP、 HTTPS)