

RG-RAP1260

Reyee Wi-Fi 6 AX3000 Dual-Band Wall Plate Access Point

DATASHEET



Highlights

- Dual-radio performance, gigabit wireless wall-mounted AP
- Better experience with MU-MIMO under 802.11ax
- Multi-Color changable Cases
- Easy installation, worldwide compatible
- Capable of Reyee Mesh and 802.11K/V
- Powerful Standalone Portal via Ruijie Cloud

/ Highlight Features

Wi-Fi 6 AX3000 Dual-Band Multi-Port Wall AP

RG-RAP1260



PoE



2.4G/5G Dual-band

3000 Mbps

3000Mbps Internet Rate

110 people

110 Recommended Concurrent Users

More Than Wi-Fi, 4 Ports Meet Multi-Task Scenarios



Latency on Video Conference? RAP1260 Makes Terminal Access Rate Up To 900Mbps.



00:09




Highlight Features

Smart AI Roaming Enhances Wireless Experience Anywhere You Go



Cloud, Make Your Business Easy

- Self-organizing network
- Cloud portal authentication
- Remote monitoring and maintenance
- Upgrade firmware via Cloud
- APP library dynamically update



Specifications

Basic Features	
Wi-Fi Standards	802.11a/n/ac/ax 802.11b/g/n/ax
MIMO	2.4 GHz, 2x2, MU-MIMO 5 GHz, 2x2, MU-MIMO
Max. Wi-Fi Speed	2.4 GHz: 574 Mbps 5 GHz: 2402 Mbps
Number of Antennas	5
Antenna Type	Built-in omnidirectional antennas
Antenna Gain	2.4 GHz: 3 dBi 5 GHz: 5 dBi
Transmit Power	EIRP: 26 dBm (2.4 GHz) 26 dBm (5 GHz) (country-specific restrictions apply) Myanmar: 2400 MHz~2483.5 MHz ≤ 20 dBm 5150 MHz~5350 MHz ≤ 23 dBm 5470 MHz~5850 MHz ≤ 25 dBm Thailand: 2400 MHz~2483.5 MHz ≤ 20 dBm 5150 MHz~5350 MHz ≤ 23 dBm 5470 MHz~5725 MHz ≤ 25 dBm 5725 MHz~5850 MHz ≤ 30 dBm
Fixed Ports	1 x 10/100/1000Base-T Ethernet uplink port 4 x 10/100/1000Base-T Ethernet downlink ports 1 x Reset hole
Max. Number of Concurrent STAs	512
Recommended Number of Concurrent STAs	110
Max. Number of SSIDs	8
Supported Frequency Bands	802.11b/g/n/ax: 2.400 GHz to 2.483 GHz 802.11a/n/ac/ax: 5.150 GHz to 5.350 GHz, 5.470 GHz to 5.725 GHz, 5.725 GHz to 5.850 GHz (country-specific restrictions apply)

Software Features	
WLAN Basic Features	
Power Adjustment	✓
Channel Bandwidth	2.4 GHz: Auto/20 MHz/40 MHz 5 GHz: Auto/20 MHz/40 MHz/80 MHz/160 MHz
Roaming	Layer 2 roaming Layer 3 roaming 802.11k/v roaming
OFDMA	✓
Beamforming	✓

/ Specifications

Software Features

Target Wake Time (TWT)*	✓
Wi-Fi Multimedia (WMM))	✓
Radar Signal Detection and Frequency Hopping (DFS)	✓
WLAN Security	
Wi-Fi Password	16 characters
Security Mode	WAP-PSK,WAP2-PSK,WPA-WAP2-PSK
Blocklist and Allowlist	✓
Enhanced User Experience	
Wi-Fi Optimization	✓
STA Limiting	✓
Removing Low-RSSI STAs	✓
Removing Low-RSSI STAs	✓
Syslog Recording Why Users Lose Connection	✓
Auto Channel and Power Adjustment on Cloud	✓
RSSI Threshold for STA Access	✓
Load Balancing	✓
Networks	
Network Access Mode	PPPoE Client DHCP Client Static IP
Avoidance of WAN IP Address Conflicts	✓
VLAN	Port-based VLAN VLAN over 802.1Q TV projection screen
DHCP Server	✓

/ Specifications

System	
Cloud Management	✓
App Management	✓
App Upgrade	✓
App Restart	✓
Scheduled Restart	✓
Default Access/Password	10.44.77.253 No Password Required by Default
Local Upgrade	✓
Online Upgrade	✓
Backup	✓
Factory Reset	✓
Language	Chinese English
System Log	✓
Diagnostics	✓
Network Check	✓
Hardware Features	
LED	1 x System status LED
Reset Hole	1 x Reset hole
Dimensions (W x D x H)	124 mm x 86 mm x 24 mm (4.88 in. x 3.89 in. x 0.94 in.)
Weight	0.5 kg (1.10 lbs)
Installation Method	In-wall mounting
Mounting Bracket Dimensions (W x D x H)	122 mm x 80 mm x 3.8 mm (4.80 in. x 3.15 in. x 0.15 in.)
Mounting Hole Pattern	Hole pattern 83.5 mm x 60 mm (3.29 in. x 2.36 in.)
Mounting Hole Diameter	2.25 mm (0.09 in.)

Specifications

Hardware Features	
Pole Diameter	N/A
Power Supply	IEEE 802.3af/at PoE
Max. Power Consumption	12 W
PoE Power Budget	N/A

Environment	
Operating Temperature	0°C to 40°C (32°F to 104°F)
Storage Temperature	−40°C to +70°C (−40°F to +158°F)
Operating Humidity	5% to 95% RH (non-condensing)
Storage Humidity	5% to 95% RH (non-condensing)
Ingress Protection Rating (IP Rating)	IP41
Surge Protection	+/-4kV
MTBF	400,000 hours

Package Contents

Package Information	RG-RAP1260
RG-RAP1260 Access Point	1
Power Adapter	N/A
User Manual	1
Cat5e UTP Cable	N/A
Mounting Bracket	1
Rack-mount Bracket	N/A
Screw	4
Certification	CE and CB
Warranty Card	1



 **R**edefine your **e**asy network

Copyright ©2000-2023 Ruijie Networks Co., Ltd. All rights reserved.

No part of this document may be reproduced or transmitted in any form or any means without prior written consent of Ruijie Networks Co., Ltd.

Notice

This content is applicable only to regions outside the China mainland. Ruijie Networks Co., Ltd. reserves the right to interpret this content.

The information contained herein is subject to change without notice. Nothing herein should be construed as constituting an additional warranty. Ruijie Networks Co., Ltd. shall not be liable for technical or editorial errors or omissions contained herein.



Ruijie Networks Co., Ltd.
Building 19, Juyuanzhou Industrial Park, No.618
Jinshan Road, Cangshan District, Fuzhou, Fujian, China
Website: <https://www.ruijienetworks.com>