



Key Features

- 4K UHD 3840 x 2160 resolution
- SuperClear® VA panel
- HDR10 delivers stellar contrast and color accuracy
- Dual HDMI and DisplayPort inputs for flexible connectivity
- Eye ProTech for comfortable viewing



Product Description

The ViewSonic VA3208-4K-HD is a 32" 4K VA monitor featuring dual HDMI and DisplayPort inputs for business and home use. The optimal screen performance and comfortable viewing are delivered through eye-care technology, and various ViewMode presets. Simply expand your workspace and experience truly seamless multitasking on just one screen with a VESA-compatible mount at low power consumption.



1. Menu Control Panel
2. Power In
3. HDMI*2
4. DisplayPort
5. Audio Out
6. VESA Compatible(Wall Mount 100 x 100mm)

Visit Us

www.viewsonic.com



DISPLAY

Display Size (in.):	32
Viewable Area (in.):	31.5
Panel Type:	VA Technology
Resolution:	3840 x 2160
Resolution Type:	UHD (Ultra HD)
Static Contrast Ratio:	3,000:1 (typ)
Dynamic Contrast Ratio:	50M:1
High Dynamic Range:	HDR10
Light Source:	LED
Brightness:	300 cd/m² (typ)
Colors:	16.7M
Color Space Support:	8 bit true
Aspect Ratio:	16:9
Response Time (Typical GTG):	4ms
Viewing Angles:	178° horizontal, 178° vertical
Backlight Life (Hours):	30000 Hrs (Min)
Curvature:	Flat
Refresh Rate (Hz):	60
Low Blue Light:	Software solution
Flicker-Free:	Yes
Color Gamut:	NTSC: 72% size (Typ) sRGB: 104% size (Typ)
Pixel Size:	0.182 mm (H) x 0.182 mm (V)
Surface Treatment:	Anti-Glare, Hard Coating (3H)

COMPATIBILITY

PC Resolution (max):	3840x2160
Mac® Resolution (max):	3840x2160
PC Operating System:	Windows 10/11 certified; macOS tested
Mac® Resolution (min):	3840x2160

CONNECTOR

3.5mm Audio Out:	1
HDMI 2.0 (with HDCP 2.2):	2
DisplayPort:	1
Power in:	DC Socket (Center Positive)

POWER

Eco Mode (Conserve):	25W
Eco Mode (optimized):	33W
Consumption (typical):	40W
Consumption (max):	42W
Voltage:	AC 100-240V
Stand-by:	0.5W
Power Supply:	External Power Adaptor

ADDITIONAL HARDWARE

Kensington Lock Slot:	1
-----------------------	---

CONTROLS

Physical Controls:	Key 1 (favorite), Key 2, Key 3, Key 4, Key 5 (power)
On Screen Display:	Input Select, Audio Adjust, ViewMode, Color Adjust, Manual Image Adjust, Setup Menu

OPERATING CONDITIONS

Temperature:	32°F to 104°F (0°C to 40°C)
Humidity (non-condensing):	20% to 90%

WALL MOUNT

VESA Compatible:	100 x 100 mm
------------------	--------------

INPUT SIGNAL

Frequency Horizontal:	HDMI (v2.0): 15 ~ 140KHz, DisplayPort (v1.4): 24 ~ 140KHz
Frequency Vertical:	HDMI (v2.0): 24 ~ 60Hz, DisplayPort (v1.4): 48 ~ 60Hz

VIDEO INPUT

Digital Sync:	TMDS - HDMI (v2.0), PCI-E - DisplayPort (v1.4)
---------------	--

ERGONOMICS

Tilt (Forward/Back):	-5° / 20°
----------------------	-----------

WEIGHT (IMPERIAL)

Net (lbs):	14.6
Net Without Stand (lbs):	12.1
Gross (lbs):	18.1

WEIGHT (METRIC)

Net (kg):	6.6
Net Without Stand (kg):	5.5
Gross (kg):	8.2

DIMENSIONS (IMPERIAL) (WXHxD)

Packaging (in.):	30.2 x 20.1 x 4.9
Physical (in.):	28.12 x 20.48 x 9.09
Physical Without Stand (in.):	28.12 x 16.83 x 2.33

DIMENSIONS (METRIC) (WXHxD)

Packaging (mm):	766 x 510 x 125
Physical (mm):	714.3 x 520.3 x 231
Physical Without Stand (mm):	714.3 x 427.48 x 59.22

GENERAL

Regulations:	CE, CE EMC, CB, RoHS, ErP, REACH, WEEE, EAC, UkrSEPRO, BSMI, VCCI, PSE, BIS
PACKAGE CONTENTS:	VA3208-4K-HD x1, HDMI Cable (v2.0; Male-Male) x1, AC/DC Adapter x1, Quick Start Guide x1, Power plug x1 or 2 (by country) for VSE
Recycle/Disposal:	Please dispose of in accordance with local, state or federal laws.
Warranty:	*Warranty offered may differ from market to market

