



230 Vac

 8 Output Schuko Italy
TO PROTECT ALL
YOUR DEVICES

- 1 On/Off switch 2 Power cable 3 Input thermal protection 4 Output sockets with child protection and blackout protection 5 Filtered output socket with child protection 6 5Vdc 2.1A USB Charger 7 USB Port 8 RJ11/45 Port

Main Specifications

- Personal Computer, Modem/Router, Cash Register, Pos
- Automatic Voltage Regulation circuit (AVR)
- USB Charger (5V 2.1A) port
- Easy replacement batteries
- Rear slots for wall mounting
- Output sockets with child protection for blackout protection
- Output sockets with child protection for overvoltage protection
- USB port
- UPS Management Software TecnoManager compatible with Windows, Mac OS X, Unix, Linux, etc.

**Specifications**

UPS Model	ERA PLUS STRIP 1.000	ERA PLUS STRIP 1.000 UK
Code	FGCERAPLS1002SCH	FGCERAPLS1002SCH
Nominal power	1,000 VA	
Active power	700 W	
Power factor	0,7	
Technology	Line Interactive with stabilizer	
Cooling	Natural	
Audible noise	< 40 dBA to 1 m	
Input connection	Fixed cable with Schuko plug	Fixed cable with UK plug
Outlets	4 UPS outputs Schuko/Italian + 4 only filtered outputs Schuko/Italian	4 UPS outputs UK + 4 only filtered outputs UK
Dimension (UPS) WxHxD	20x10x34,5 cm	
Dimension (with packing) WxHxD	26,9x14,6x42,5 cm	
Weight	4,4 Kg	
Input		
Number of phases	1Ph+N	
Nominal voltage	Single-phase 230Vac	
Input voltage range	+20%/-25%	
Nominal frequency	50/60 Hz (automatic selection)	
Input frequency range	+/-5%	
Output		
Number of phases	1Ph+N	
Nominal voltage	Single-phase 230Vac	
Voltage regulation (Line mode)	AVR (Automatic Voltage Regulation)	
Voltage regulation (Battery mode)	+/-5%	
Frequency	50/60 Hz (automatic selection)	
Inverter waveform	Modified sinewave	
Overload capability	< 130%	
Transfer time	2 ms (typical)	
Battery		
Type	Lead acid, sealed, maintenance free	
Backup time (typical)	10-40 min	
Environmental specification		
Working temperature	From 0 to 40 °C (retcomended from 20 to 25 °C)	
Humidity	< 95% without condensation	
Maximum altitude	3000 m	
IP protection	IP20	
Certifications	CE (Standards: Low Voltage Directive IEC EN 62040-1; EMC Directive IEC EN 62040-2; classification IEC EN 62040-3)	

© 2021 Tecnoware Power Systems. The technical data may change without prior notice.

Available on request with input/output nominal voltage 110Vac or 120Vac and with input plug and output sockets for specific country.