



## Equip LC/ST 50/125µm 10m InfiniBand/fibre optic cable Orange

**Brand :** Equip

**Product code:** 254216

**Product name :** LC/ST 50/125µm 10m

- Duplex single-mode fiber optic cable
  - Connector: Ceramic Ferrule
  - Core diameter: 9/125µm
  - Cable Spec: I-VH 2 x 1G
  - Low Smoke Zero Halogen (LSZH/LSOH)
  - Cable jacket color: Orange
- LC/ST Fiber Optic Patch Cable, OM2, 10m



### Equip LC/ST 50/125µm 10m InfiniBand/fibre optic cable Orange:

The equip®Fiber Optic Patch Cord is made of superior materials to ensure an insertion loss, return loss, and endface geometry connection. The Fiber Optic Patch Cord series comes with a comprehensive collection of lengths and connectors to fulfill your demand for the deployment.

- Multi-mode, duplex
- Connector: ceramic-ferrule
- Cladding: low smoke and zero halogen
- Cable spec: I-VH 2 x 1G
- Cable jacket color: orange
- Each cable includes a measure protocol
- OM1 = 62.5/125µm, OM2 = 50/125µm

Equip LC/ST 50/125µm 10m. Cable length: 10 m, Fibre optic type: OM2, Connector 1: LC, Connector 2: ST, Core diameter: 50 µm, Full duplex

| Features             |        | Features                      |                               |
|----------------------|--------|-------------------------------|-------------------------------|
| Cable length *       | 10 m   | Fiber mode structure          | Multi-mode                    |
| Fibre optic type     | OM2    | Insertion loss                | 0.5 dB                        |
| Connector 1 *        | LC     | Jacket material *             | Low smoke zero halogen (LSZH) |
| Connector 2 *        | ST     | <b>Certificates</b>           |                               |
| Connector 1 gender * | Male   | Compliance certificates       | REACH, RoHS                   |
| Connector 2 gender * | Male   | <b>Operational conditions</b> |                               |
| Product colour *     | Orange | Operating temperature (T-T)   | -20 - 70 °C                   |
| Full duplex          | ✓      | Storage temperature (T-T)     | -40 - 80 °C                   |
| Core diameter        | 50 µm  | <b>Logistics data</b>         |                               |
| Cladding diameter    | 125 µm | Harmonized System (HS) code   | 85447000                      |



4015867132838

### **Catalog Object Cloud**



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.