

GIGABYTE GP-AP850GM power supply unit 850 W 20+4 pin ATX Black

Brand : GIGABYTE

Product code: 28200-AP85GM-1EUR

Product name : GP-AP850GM

- Fully Modular Design
- High quality 100% Japanese Capacitors
- 135mm 2 ball bearing smart fan with fan stop function
- 80 PLUS Gold certified: above 90% efficiency at 50% load
- Single +12V rail
- OCP/OTP/OVP/OPP/UVP/SCP protection
- 10 years warranty (Adjusted according to different regions)

Fully Modular, 850 W, ATX 12V v2.31, Active PFC, 100 - 240 V, 47 - 63 Hz, 10 A, 150 x 160 x 86 mm
 GIGABYTE GP-AP850GM. Total power: 850 W, AC input voltage: 100 - 240 V, AC input frequency: 47 - 63 Hz. Motherboard power connector: 20+4 pin ATX, Motherboard power cable length: 65 cm, SATA power cable length: 450,550,650,750 mm. Purpose: PC, Power supply unit (PSU) form factor: ATX, 80 PLUS certification: 80 PLUS Gold. Product colour: Black, Fan diameter: 13.5 cm, Number of fans: 1 fan(s). Width: 150 mm, Depth: 160 mm, Height: 86 mm



Power		Ports & interfaces	
Total power *	850 W	PCI Express power connectors (6+2 pin)	6
AC input voltage *	100 - 240 V	CPU power connector (4+4 pin)	✓
AC input frequency	47 - 63 Hz	ATX power connector (20+4 pin)	✓
Input current	10 A	Floppy drive power connector	2
Power factor	0.9	Floppy disk drive connector	✓
Power Factor Correction (PFC) type	Active	PCI Express connector	✓
Combined power (+3.3V)	120 W	Cabling type	Fully-Modular
Combined power (+12V)	846 W	Performance	
Combined power (+5V)	120 W	80 PLUS certification *	80 PLUS Gold
Combined power (-12V)	3.6 W	Purpose *	PC
Combined power (+5Vsb)	15 W	Power supply unit (PSU) form factor *	ATX
Max output current (+3.3V)	20 A	ATX version	2.31
Max output current (+12V)	70.5 A	Mean time between failures (MTBF)	100000 h
Max output current (+5V)	20 A	Design	
Max output current (-12V)	0.3 A	Product colour	Black
Max output current (+5Vsb)	3 A	Fan diameter	13.5 cm
Hold time	16 ms	Number of fans	1 fan(s)
Efficiency	90%	Fan location	Top
Power Good signal delay range	100 - 150 ms	On/off switch	✓
Power protection features	Over current, Over power, Over voltage, Overheating, Short circuit, Under voltage	Weight & dimensions	
Ports & interfaces		Width	150 mm
Motherboard power connector *	20+4 pin ATX	Depth	160 mm
Motherboard power cable length	65 cm	Height	86 mm
Number of SATA power connectors	6	Packaging data	
SATA power cable length	450,550,650,750 mm	Package type	Box
Peripheral (Molex) power connectors (4-pin) *	6		

Ports & interfaces		Logistics data	
EPS power connector (8-pin)	✓	Harmonized System (HS) code	84733020



4719331550912

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.