


Viewsonic 86" 4K Commercial Display with ProAV Integration

Brand : Viewsonic

Product code: CDE8614-2C

Product name : 86" 4K Commercial Display with ProAV Integration



- Quad-Core SoC with 4 GB RAM delivers smooth, stable performance
 - Fast warm boot launches signage and content in under seven seconds
 - USB playback with signal failover ensures continuous content delivery
 - 4K UHD in any orientation provides sharp, professional visuals
 - 500-nit brightness and 24/7 operation support reliable round-the-clock signage
 - ProAV integration and remote control via ViewSonic Manager and leading platforms
- 86", 4K UHD (3840 x 2160), TFT LCD, DLED, 500 nits, 2000:1, 8 ms, Quad-core ARM Cortex-A73, 4GB, 32GB, 2x 10 W, HDMI 2.1, RS-232, WIFI slot, SPDIF, RJ45, USB-A, USB-C, 3.5 mm, Android 14 AOSP
Viewsonic 86" 4K Commercial Display with ProAV Integration. Product design: Digital signage flat panel.
Display diagonal: 2.18 m (86"), Display technology: LCD, Display resolution: 3840 x 2160 pixels, Display brightness: 500 cd/m², HD type: 4K Ultra HD. Wi-Fi. Operating hours (hours/days): 24/7. Operating system installed: Android 14. Product colour: Black

Display		Design	
Panel type	TFT	Anti-glare screen	✓
LED backlight	✓	Performance	
LED backlighting type	Direct-LED	Purpose *	Commercial
Display diagonal *	2.18 m (86")	Operating hours (hours/days)	24/7
Display technology *	LCD	Power	
Display resolution *	3840 x 2160 pixels	Power consumption (typical) *	120.95 W
Display brightness *	500 cd/m ²	Energy efficiency class (SDR)	E
HD type *	4K Ultra HD	AC input voltage	100 - 240 V
Touchscreen *	✗	Energy efficiency scale	A to G
Native aspect ratio	16:9	Computer system	
Response time	8 ms	Built-in processor *	✓
Contrast ratio (typical)	1200:1	Processor manufacturer	ARM
Contrast ratio (dynamic)	2000:1	Processor architecture	ARM Cortex-A73
Viewing angle, horizontal	178°	Processor cores	4
Viewing angle, vertical	178°	Internal memory	4 GB
Active display area (W x H)	1895.04 x 1065.96 mm	Internal storage capacity	32 GB
Panel life	50000 h	Operating system installed	Android 14
Native refresh rate	60 Hz	Weight & dimensions	
Haze rate	25%	Display width	1930.8 mm
Surface hardness	3H	Display depth	68 mm
Ports & interfaces		Display height	1101.7 mm
HDMI ports quantity *	4	Display weight	42 kg
HDMI version	2.1	Weight	42 kg
HDMI input ports quantity	3	Packaging data	
HDMI output ports quantity	1	Package width	2110 mm
DVI port *	✗	Package depth	225 mm
DisplayPort version	1.2	Package height	1247 mm
USB port *	✓	Package weight	57 kg
USB ports quantity	3	Packaging content	
USB version	2.0	Remote control included	✓
USB connector type	USB Type-A, USB Type-C	Batteries included	✓
USB Power Delivery (USB PD)	✓	Cables included	AC, HDMI, RS-232
USB Power Delivery up to	15 W	Mounting kit	✓
USB Type-C DisplayPort Alternate Mode	✓		
Ethernet LAN (RJ-45) ports	1		
RS-232 interface	✓		

Ports & interfaces		Operational conditions	
Digital audio optical out	1	Operating temperature (T-T)	0 - 40 °C
PC Audio out	✓	Operating relative humidity (H-H)	20 - 80%
Audio		Logistics data	
Built-in speaker(s) *	✓	Products per master (outer) case	1 pc(s)
Number of built-in speakers	2	Pallet gross length	114 cm
RMS rated power	20 W	Pallet gross width	2.14 m
Design		Pallet gross height	136.7 cm
Product design *	Digital signage flat panel	Harmonized System (HS) code	8528521000
Placement supported *	Indoor	Network	
Orientation	Horizontal/Vertical	Ethernet LAN *	✓
Product colour *	Black	Ethernet LAN data rates	10,100,1000 Mbit/s
Screen shape	Flat	Wi-Fi *	✓
VESA mounting *	✓	Technical details	
Panel mounting interface	600 x 400 mm	Sustainability certificates	ENERGY STAR, EPEAT Gold, ErP
Bezel width (bottom)	1.59 cm	Compliance certificates	CB, CE, EAC, Federal
Bezel width (side)	1.59 cm		Communications Commission (FCC),
Bezel width (top)	1.59 cm		RCM, REACH, RoHS, WEEE, cTUVus
		Other features	
		Bundled software	AirSync, Manager



766907036381

Catalog Object Cloud