

Philips 6000 series 27B2U6903/00 computer monitor 68.6 cm (27") 3840 x 2160 pixels 4K Ultra HD LED Anthracite

Brand : Philips

Product family: 6000 series

Product code: 27B2U6903/00

Product name : 27B2U6903/00

Business Monitor 27B2U6903 4K UHD monitor with Thunderbolt™ 4

Philips 6000 series 27B2U6903/00 computer monitor 68.6 cm (27") 3840 x 2160 pixels 4K Ultra HD LED Anthracite:

This monitor introduces you to lightning-fast connectivity. With its Thunderbolt 4 port, Smart KVM feature and 4K UHD resolution, this combination offers power delivery, source switching and beautiful imagery in one monitor.

Philips 6000 series 27B2U6903/00. Display diagonal: 68.6 cm (27"), Display resolution: 3840 x 2160 pixels, HD type: 4K Ultra HD, Display technology: LED, Response time: 4 ms, Native aspect ratio: 16:9, Viewing angle, horizontal: 178°, Viewing angle, vertical: 178°. Built-in speaker(s). Built-in USB hub, USB hub version: 3.2 Gen 2 (3.1 Gen 2). VESA mounting, Height adjustment. Product colour: Anthracite



Display		Ports & interfaces	
Display diagonal *	68.6 cm (27")	Thunderbolt 4 ports quantity	2
Display resolution *	3840 x 2160 pixels	Headphone out *	✓
HD type *	4K Ultra HD	Microphone in	✓
Native aspect ratio *	16:9	HDCP	✓
Display technology *	LED	HDCP version	1.4/2.2
Panel type *	IPS	Network	
LED backlight	✓	Ethernet LAN	✓
Backlight type	RGB LED	Ergonomics	
Touchscreen *	✗	VESA mounting *	✓
Display brightness (typical)	350 cd/m²	Panel mounting interface	100 x 100 mm
Response time *	4 ms	Cable lock slot *	✓
Response time measurement type	GTG (Gray to Gray)	Cable lock slot type	Kensington
Anti-glare screen	✓	Height adjustment *	✓
Screen shape *	Flat	Adjustable height (max)	15 cm
Contrast ratio (typical) *	1000:1	Swivelling	✓
Contrast ratio (dynamic)	50000000:1	Swivel angle range	-180 - 180°
Maximum refresh rate *	60 Hz	Tilt adjustment	✓
Viewing angle, horizontal	178°	Tilt angle range	-5 - 30°
Viewing angle, vertical	178°	Picture-in-Picture	✓
Display number of colours *	1.07 billion colours	On Screen Display (OSD)	✓
Pixel density	163 ppi	On Screen Display (OSD) languages	Simplified Chinese, Traditional Chinese, Czech, German, Dutch, English, Spanish, Finnish, French, Greek, Hungarian, Italian, Japanese, Korean, Polish, Portuguese, Russian, Swedish, Turkish, Ukrainian
Viewable size, horizontal	59.7 cm		
Viewable size, vertical	33.6 cm	Number of OSD languages	21
Digital horizontal frequency	30 - 140 kHz	Plug and Play	✓
Digital vertical frequency	23 - 75 Hz		
Display diagonal (metric)	68.5 cm		
DDC/CI	✓		
Haze rate	25%		

Display		Ergonomics	
Surface hardness	3H	LED indicators	Operation, Stand-by
Performance		Power	
VESA Adaptive Sync support	✓	Energy efficiency class (SDR) *	E
Component video sync	Separate Sync, Sync-on-green (SOG)	Power consumption (typical) *	28.6 W
Flicker-free technology	✓	Power consumption (standby) *	0.45 W
Low Blue Light technology	✓	Power consumption (off)	0.4 W
Multimedia		AC input voltage	100 - 240 V
Number of speakers	2	AC input frequency	50/60 Hz
RMS rated power	6 W	Power supply type	Internal
Built-in speaker(s) *	✓	Operational conditions	
Built-in camera *	✗	Operating temperature (T-T)	0 - 40 °C
Design		Storage temperature (T-T)	-20 - 60 °C
Market positioning *	Office	Operating relative humidity (H-H)	20 - 80%
Product colour *	Anthracite	Storage relative humidity (H-H)	20 - 80%
Feet colour	Charcoal	Operating altitude	0 - 3658 m
Ports & interfaces		Non-operating altitude	0 - 12192 m
Built-in USB hub *	✓	Weight & dimensions	
USB hub version	3.2 Gen 2 (3.1 Gen 2)	Width (with stand)	613 mm
USB upstream port type	USB Type-C	Depth (with stand)	230 mm
Number of upstream ports	2	Height (with stand)	544 mm
USB Type-A downstream ports quantity	4	Weight (with stand)	7.15 kg
USB Type-C downstream ports quantity	2	Width (without stand)	613 mm
USB Type-C DisplayPort Alternate Mode	✓	Depth (without stand)	59 mm
USB Power Delivery (USB PD)	✓	Height (without stand)	371 mm
USB Power Delivery up to	100 W	Weight (without stand)	5.1 kg
HDMI *	✓	Packaging data	
HDMI ports quantity	2	Package width	780 mm
HDMI version	2.0	Package depth	161 mm
DisplayPorts quantity	1	Package height	480 mm
DisplayPort version	1.4	Package weight	10.2 kg
		Packaging content	
		Stand included	✓
		Cables included	AC, DisplayPort, HDMI, Thunderbolt
		Manual	✓
		Other features	
		Compliance certificates	CB, CE, EAC, Federal Communications Commission (FCC), GS mark, ICES, RoHS, TÜV mark, UKCA



8712581804749

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.