

Epson Coated Paper 95, 914mm x 45m

Brand : Epson

Product code: C13S045285

Product name : Coated Paper 95, 914mm x 45m



Coated Paper 95, 914mm x 45m

Epson Coated Paper 95, 914mm x 45m:

Specially developed for CAD and GIS inkjet plotting with dye or pigment-based ink, this robust, top-of-the-range paper is also suitable for graphics and business presentations. It shows crisp lines, sharp characters from 1mm and yields high-contrast colour. High opacity and quick drying times bring visual impact and convenience in handling, while strong resistance to water makes it smudge-proof

- Top-of-the-range plotting paper for CAD, GIS, business presentations and graphics
- Water resistant and smudge-proof
- High opacity
- Fast drying
- Shows sharp lines and high-contrast colour
- Works well with dye and pigment ink

Features		Packaging data	
Roll length *	45 m	Quantity per pack	1 pc(s)
Roll width *	91.4 cm	Package width	110 mm
Size (imperial)	91.4 cm (36")	Package depth	940 mm
Finish type *	Matte	Package height	108 mm
Print media weight *	95 g/m²	Package weight	4.4 kg
Paper brightness	98	Other features	
Paper whiteness	145		
Printing material brightness	I*91/a 4/b -15, ISO 98%	Compatible products Epson Stylus Pro 10600, Stylus Pro 11880, Stylus Pro 9450, Stylus Pro 9500, Stylus Pro 9600, Stylus Pro 9700, Stylus Pro 9880, Stylus Pro 9890, Stylus Pro 9900	
Country of origin	China		
Printing material whiteness	CIE 145%		
Technical features	Epson Stylus Pro 10600, Stylus Pro 11880, Stylus Pro 9450, Stylus Pro 9500, Stylus Pro 9600, Stylus Pro 9700, Stylus Pro 9880, Stylus Pro 9890, Stylus Pro 9900	Logistics data	
		Products per pallet	42 pc(s)
		Harmonized System (HS) code	84439990
		Pallet width (UK)	100 cm
		Pallet length (UK)	120 cm
		Pallet height (UK)	74.4 cm
		Pallet gross width	80 cm
		Pallet gross length	120 cm
		Pallet gross height	74.4 cm
		Products per pallet (UK)	48 pc(s)
		Products per pallet layer	7 pc(s)
		Products per pallet layer (UK)	8 pc(s)
		Minimum order quantity	2 pc(s)
Operational conditions			
Operating relative humidity (H-H)	40 - 60%		
Operating temperature (T-T)	15 - 30 °C		
Storage temperature (T-T)	0 - 40 °C		
Storage relative humidity (H-H)	10 - 80%		



8715946491226

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.