

## Epson TM-J7700(321) W/O MICR,WHITE, INC PSU, EU

**Brand :** Epson

**Product code:** C31CF70321

**Product name :** TM-J7700(321) W/O MICR,WHITE, INC PSU, EU

- Versatile inkjet POS printer: Faster, better quality and more versatile
- Low TCO: Similar overall costs to previous dot matrix model
- Durable prints: Print is now more resistant to water and light
- Simple maintenance: Ink and paper rolls are very easy to replace
- Backwards compatible: Crisp, clear text and glossy photos

TM-J7700(321) W/O MICR,WHITE, INC PSU, EU

Epson TM-J7700(321) W/O MICR,WHITE, INC PSU, EU. Print technology: Inkjet, Type: POS printer, Print speed: 98 mm/sec. Supported paper width: 58 - 83 mm, Media thickness: 0.06 - 0.09 mm, Maximum paper size (slip): 230 x 297 mm. Connectivity technology: Wired, USB connector: USB Type-B. Ethernet LAN data rates: 10,100 Mbit/s. Sound pressure level (printing): 55 dB, Mean time between failures (MTBF): 180000 h, Autocutter durability: 1.5 million cuts



| Printing                          |                        | Features                          |                                                                                                                   |
|-----------------------------------|------------------------|-----------------------------------|-------------------------------------------------------------------------------------------------------------------|
| Colour                            | ✗                      | Certification                     | CE, EN55024, EN55032 Class A, IEC61000-4-2, IEC61000-4-3, IEC61000-4-4, IEC61000-4-5, IEC61000-4-6, IEC61000-4-11 |
| Print speed                       | 98 mm/sec              |                                   |                                                                                                                   |
| Print speed (graphic)             | 98 mm/sec              |                                   |                                                                                                                   |
| Print speed (receipt)             | 98 mm/sec              |                                   |                                                                                                                   |
| Print speed (slip)                | 85 mm/sec              |                                   |                                                                                                                   |
| Printing characters               | Text, Graphic, Barcode | Design                            |                                                                                                                   |
| Character sets                    | ANK                    | Product colour *                  | Black                                                                                                             |
| Alphanumeric memory               | 95                     | Power                             |                                                                                                                   |
| Print technology *                | Inkjet                 | Power source type *               | DC                                                                                                                |
| Type *                            | POS printer            | AC input voltage                  | 24 V                                                                                                              |
|                                   |                        | Power consumption (standby)       | 70000 mA                                                                                                          |
| Paper handling                    |                        | Operational conditions            |                                                                                                                   |
| Supported paper width             | 58 - 83 mm             | Operating temperature (T-T)       | 10 - 35 °C                                                                                                        |
| Media thickness                   | 0.06 - 0.09 mm         | Storage temperature (T-T)         | -20 - 40 °C                                                                                                       |
| Maximum paper size (slip)         | 230 x 297 mm           | Operating relative humidity (H-H) | 20 - 80%                                                                                                          |
|                                   |                        | Storage relative humidity (H-H)   | 20 - 85%                                                                                                          |
| Ports & interfaces                |                        | Weight & dimensions               |                                                                                                                   |
| USB port *                        | ✓                      | Width                             | 251 mm                                                                                                            |
| USB 2.0 ports quantity            | 1                      | Depth                             | 260 mm                                                                                                            |
| USB connector                     | USB Type-B             | Height                            | 188 mm                                                                                                            |
| Connectivity technology *         | Wired                  | Weight                            | 5.8 kg                                                                                                            |
| Ethernet LAN (RJ-45) ports        | 1                      |                                   |                                                                                                                   |
| Network                           |                        | Packaging data                    |                                                                                                                   |
| Ethernet LAN *                    | ✓                      | Cables included                   | AC                                                                                                                |
| Ethernet LAN data rates           | 10,100 Mbit/s          | Quantity per pack                 | 1 pc(s)                                                                                                           |
| Wi-Fi *                           | ✗                      | Package width                     | 355 mm                                                                                                            |
|                                   |                        | Package depth                     | 390 mm                                                                                                            |
|                                   |                        | Package height                    | 310 mm                                                                                                            |
|                                   |                        | Package weight                    | 7.87 kg                                                                                                           |
| Features                          |                        |                                   |                                                                                                                   |
| Sound pressure level (printing)   | 55 dB                  |                                   |                                                                                                                   |
| Mean time between failures (MTBF) | 180000 h               |                                   |                                                                                                                   |

| Features                  |                      | Logistics data                      |               |
|---------------------------|----------------------|-------------------------------------|---------------|
| Half-cutter               | ✗                    | Pallet weight (UK)                  | 0 g           |
| Autocutter durability     | 1.5 million cuts     | Harmonized System (HS) code         | 84433210      |
| Country of origin         | China                | Products per pallet                 | 36 pc(s)      |
| Printer receipt unit life | 3700000000 lines     | Pallet gross weight                 | 0 g           |
| Printer slip unit life    | 5000000 lines        | Products per pallet (UK)            | 36 pc(s)      |
| Safety                    | TÜV, TÜV (EN60950-1) | Technical details                   |               |
|                           |                      | Font styles                         | ANK           |
|                           |                      | Other features                      |               |
|                           |                      | Paper dimensions                    | 58 mm - 83 mm |
|                           |                      | Mean cycles between failures (MCBF) | 5000000       |



8715946639079

### Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.