



Dahua Technology DHI-ASI3203E access control reader Basic access control reader Black

Brand : Dahua Technology

Product code: DHI-ASI3203E

Product name : DHI-ASI3203E

- Comes with a 2.4 inch LCD with a resolution of 320 (H) × 240 (V)
 - 2-MP CMOS dual-lens camera with IR illumination and DWDR
 - Multiple unlock methods including face, IC card and password. You can configure scheduled unlock methods, or combine them to create your own personal unlock methods
 - Supports 1,000 users, 1,000 faces, 3,000 cards, 1,000 passwords, 50 administrators, and 100,000 records
 - Recognizes faces 0.3 m to 1.5 m away (0.98 ft-4.92 ft) at an accuracy of 99.9%, and compares 1 face with N faces at the speed of 0.2 seconds per person
 - Supports security extension modules for access control, preventing doors from being forcefully opened
 - Supports Web attendance management and exporting local attendance reports
 - Supports doorbell
 - TCP/IP connection
 - Provides power to the electromagnetic lock and card reader (max 12 V, 1 A)
- Single Door Face Recognition Access Controller

Technical details		Ports & interfaces	
Type *	Basic access control reader	Ethernet LAN (RJ-45) ports	1
Authentication type *	Access chip/card, Biometric, Face recognition, Password	Supported network protocols	IPv4;RTSP;UDP;P2P;IPv6;RTP;TCP
Fingerprint reader *	✗	PC connected *	✓
Access code reader *	✓	RS-485 ports	1
Access chip/card reader *	✓	USB port	✓
Alarm function	✓	Power	
Face capacity	1000	Input voltage	12 V
Face recognition distance	1.2 - 2 m	Input current	2 A
Face recognition accuracy	99%	Power consumption (typical)	12 W
User capacity	1000 user(s)	Weight & dimensions	
Password capacity	1000	Width	184.9 mm
Record capacity	100000	Depth	76.2 mm
Product colour	Black	Height	20.5 mm
Housing material	Acrylonitrile butadiene styrene (ABS), Polycarbonate (PC)	Weight	600 g
Display		Packaging data	
Built-in display *	✓	Package width	219 mm
Display diagonal	6.1 cm (2.4")	Package depth	122 mm
Maximum resolution	320 x 240 pixels	Package height	58 mm
Screen shape	Flat	Operational conditions	
Touchscreen	✗	Operating temperature (T-T)	-10 - 45 °C
Camera		Operating relative humidity (H-H)	0 - 90%
Front camera *	✓	Storage temperature (T-T)	-20 - 70 °C
Front camera type	Dual camera	Storage relative humidity (H-H)	30 - 75%
Sensor type	CMOS		
Total megapixels	2 MP		
Wide Dynamic Range (WDR)	✓		

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.