




Cat6a 10G Shielded Toolless Slim Keystone Jack, Orange

For Easy and Quick Snap-in Deployment in High-density Patch Panels, STP, for Solid Wire, Gold-plated Contacts, Metal Housing

Part No.: **791328**

EAN-13: 0766623791328 | UPC: 766623791328

Cat6a STP Slimline Keystone Jack for easy, fast and tool-free deployment with comfortable fit in high-density patch panels

The Cat6a 10G Shielded Toolless Slim Keystone Jack, Black from Intellinet Network Solutions is designed for quick, seamless side-by-side deployment. Without any special tools, this module easily snaps into blank patch panels, wall plates or surface connection boxes. It is suitable for solid conductor cables in high-performance network applications up to 10GBase-T and PoE applications up to IEEE802.3bt / PoE++ / 4PPoE / Ultra PoE. For maximum signal integrity, it is equipped with gold-plated contacts and 360° STP shielding.

Features:

- For easy, time-saving and tool-free deployment in blank patch panels, wall plates or surface connection boxes
- Slimline design, only 14.8 mm (0.58 in.) wide for comfortable side-by-side installation
- Cat6a Class EA RJ45 module with 10G and 500 MHz in accordance with ISO/IEC 11801
- STP 360° shielded RJ45 module for PoE applications up to IEEE802.3bt /

PoE++ / 4PPoE / Ultra PoE

- 6 micro-inch gold-plated contacts
- Supports solid wire with 22/1 to 26/1 AWG
- Standard 8P8C design, compatible with all network RJ45 connections
- Compatible and color-coded with T568A and T568B
- Fully backward compatible with all the previous cable categories, including Category 6, 5e and 5
- Cable tie included
- Lifetime warranty

Specifications:

Standards and Certifications

- CE
- RoHS
- ISO/IEC 11801
- REACH
- UKCA

General

- Supports transfer speeds up to 10 Gbps
- Max. operating frequency: 500 MHz
- Supports all PoE standards up to IEEE802.3bt / PoE++ / 4PPoE / Ultra PoE
- Mating cycles: ≥ 750
- Insertion force: 30N max.
- Retention strength: 7.7 kg (17 lbs.) between jack and plug
- Suitable for cables with solid wire: 22/1 to 26/1 AWG, OD 6.0 to 8.0 mm

Material

- Contacts: phosphor bronze
- Contact plating: 6 micro-inch gold
- IDC: phosphor bronze
- Housing: zinc alloy die casting

Electrical

- Insulation resistance: ≥ 500 MOhm
- Dielectric withstanding voltage: 1,000 V DC/700 V AC
- Contact resistance: ≤ 20 MOhm
- DC resistance: ≥ 0.3 Ohm
- Current rating: 1.5 A

Physical

- Dimensions (L x W x H): 36 x 14.8 x 20 mm (1.41 x 0.58 x 0.79 in.)
- Net weight: 12 g (0.42 oz.)
- Gross weight: 24 g (0.85 oz.)

Environmental

For more information on Intellinet products, consult your local dealer or visit www.intellinet-network.com.

All names of products or services mentioned herein are trademarks or registered trademarks of their respective owners. Distribution and reproduction of this document, and use and disclosure of the contents herein, are prohibited unless specifically authorized.

- Operating temperature: -10 - 60°C (14 - 140°F)
- Storage temperature: -40 - 70°C (-40 - 158°F)
- Operating humidity (non-condensing): 10 - 90% RH

Package Contents

- Cat6a 10G Shielded Toolless Slim Keystone Jack
- Cable tie
- Instructions



