



**ACT 5 meter Singlemode 9/125 OS2 Preterm fiber cable 24F LC Polarity Twist**

**Brand :** ACT

**Product code:** DC5551

**Product name :** 5 meter Singlemode 9/125 OS2 Preterm fiber cable 24F LC Polarity Twist

- Up to 80% less installation time
  - Change polarity in a few seconds with the Polarity twist connector
  - Easy cablemanagement with compact fanoutkits
  - Includes an individual testreport on IL and en 5 years warranty
  - No investment in fusion splicing or test equipment
  - Connectors are protected by protective tube during installation
  - Connectors are installed in a cleanroom production environment
  - Easily install cable by optional separable cable glands
- 5 meter Singlemode 50/125 OS2 Preterm fiber cable 24F LC Polarity Twist


**ACT 5 meter Singlemode 9/125 OS2 Preterm fiber cable 24F LC Polarity Twist:**

For fast and easy installation of installation and backbone cabling in your datacenter choose ACT preterm cabling

**ACT for all your MAC (Moves Adds and Changes)**

Unique is that ACT keeps stock of preterm fiber cabling. For you this means you can start directly if you want to change or expand your backbone cabling

ACT 5 meter Singlemode 9/125 OS2 Preterm fiber cable 24F LC Polarity Twist. Cable length: 5 m, Fibre optic type: OS2, Connector 1: LC, Connector 2: LC, Core diameter: 9 µm



| Features             |             | Features                    |             |
|----------------------|-------------|-----------------------------|-------------|
| Cable length *       | 5 m         | Insertion loss              | 0.15 dB     |
| Fibre optic type     | OS2         | Return loss                 | 55 dB       |
| Connector 1 *        | LC          | Operational conditions      |             |
| Connector 2 *        | LC          | Operating temperature (T-T) | -20 - 70 °C |
| Connector 1 gender * | Male        | Weight & dimensions         |             |
| Connector 2 gender * | Male        | Cable diameter              | 5 mm        |
| Product colour *     | Yellow      | Packaging content           |             |
| Core diameter        | 9 µm        | Quantity per pack           | 1 pc(s)     |
| Cladding diameter    | 125 µm      | Logistics data              |             |
| Fiber mode structure | Single-mode | Harmonized System (HS) code | 85447000    |



8716065454376

### **Catalog Object Cloud**



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.