

CyberPower CP1600EIPFCLCD uninterruptible power supply (UPS) Line-Interactive 1.6 kVA 1000 W 6 AC outlet(s)

Brand : CyberPower

Product code: CP1600EIPFCLCD

Product name : CP1600EIPFCLCD

CyberPower CP1600EIPFCLCD. UPS topology: Line-Interactive, Output power capacity: 1.6 kVA, Output power: 1000 W. AC outlet types: C13 coupler, Type F, Power plug: C14 coupler, AC outlets quantity: 6 AC outlet(s). Battery technology: Sealed Lead Acid (VRLA), Typical backup time at full load: 2.6 min, Typical backup time at half load: 9.7 min. Form factor: Tower, Product colour: Black, Cable length: 1.83 m. Compliance certificates: CE, RoHS



Features		Battery	
UPS topology *	Line-Interactive	Typical backup time at half load	9.7 min
Output power capacity *	1.6 kVA	Battery recharge time	8 h
Output power *	1000 W	Design	
Waveform *	Pure sine	Form factor *	Tower
Input operation voltage (min) *	169 V	Cable length	1.83 m
Input operation voltage (max) *	271 V	Product colour *	Black
Input frequency *	50/60 Hz	Control type	Buttons
Output frequency	50/60 Hz	Display type	LCD
Automatic Voltage Regulation (AVR)	✓	LED indicators	✓
Maximum current	10 A	Operational conditions	
Surge energy rating	405 J	Operating temperature (T-T)	0 - 40 °C
Response time	8 ms	Storage temperature (T-T)	-15 - 45 °C
Heat dissipation	24 BTU/h	Operating relative humidity (H-H)	0 - 95%
Power Factor Correction (PFC) type	Active	Storage relative humidity (H-H)	0 - 95%
Surge protection	✓	Operating altitude	0 - 3000 m
Audible alarm(s)	✓	Non-operating altitude	0 - 15000 m
Audible alarm modes	Alarm when on battery, Fault, Low battery alarm, Overload alarm	Certificates	
Power source type	AC	Compliance certificates	CE, RoHS
Detachable power cord	✓	Packaging content	
Socket circuit breaker	✓	Batteries included	✓
Ports & interfaces		Quick installation guide	✓
AC outlet types	C13 coupler, Type F		

Ports & interfaces		Sustainability	
Power plug	C14 coupler	Sustainability compliance	✓
AC outlets quantity	6 AC outlet(s)	Weight & dimensions	
USB port	✓	Width	100 mm
USB 2.0 ports quantity	2	Depth	355 mm
USB port type	USB Type A/USB Type-C	Height	280 mm
Serial interface	✓	Weight	11 kg
Ethernet LAN (RJ-45) ports	2	Packaging data	
Battery		Package width	195 mm
Battery technology	Sealed Lead Acid (VRLA)	Package depth	466 mm
Typical backup time at full load	2.6 min	Package height	370 mm
		Package weight	13 kg
		Other features	
		Nominal output voltage	230 V
		Nominal input voltage	220-240 V
		Overload protection	✓



4711027797946

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.