

Hisense PX3 projection TV Ultra short throw projector 2800 ANSI lumens UHD 4K (3840x2160) Black, Dark Grey

Brand : Hisense

Product code: 20014749

Product name : PX3

Hisense PX3. Projector brightness: 2800 ANSI lumens, Projector native resolution: UHD 4K (3840x2160), Contrast ratio (typical): 3000:1. Light source type: Laser. HD type: 4K Ultra HD, Display refresh rates supported: 50 Hz, 60 Hz. HDMI version: 2.0/2.1. Wi-Fi standards: 802.11a, 802.11b, 802.11g, Wi-Fi 4 (802.11n), Wi-Fi 5 (802.11ac)



Projector		Features	
Projector brightness *	2800 ANSI lumens	Product colour *	Black, Dark Grey
Projector native resolution *	UHD 4K (3840x2160)	High Dynamic Range (HDR) supported	✓
Contrast ratio (typical) *	3000:1	High Dynamic Range (HDR) technology	High Dynamic Range 10 (HDR10), High Dynamic Range 10+ (HDR10 Plus), Hybrid Log-Gamma (HLG)
Native aspect ratio *	16:9	4K Ultra HD upscaling	✓
Smart projector	✓	Operating system installed	VIDAA U
Screen size compatibility *	2032 - 3810 mm (80 - 150")	Operating system version	7
Light source		Video apps	Amazon Prime Video, Disney+, Netflix, YouTube
Light source type *	Laser	Video formats supported	3GP, AVI, FLV, MKV, MOV, MP4, MPEG, MPG, OGM, VOB, WMV
Lens system		Audio formats supported	AAC, FLAC, MP2, MP3, MP4, WAV, WMA
Throw ratio	0.22	Image formats supported	BMP, GIF, JPEG, PNG
Video		Multimedia	
3D *	✗	Built-in speaker(s) *	✓
HD type	4K Ultra HD	RMS rated power	50 W
Display refresh rates supported	50 Hz, 60 Hz	Number of built-in speakers	4
Ports & interfaces		Audio decoders	Dolby Atmos
HDMI version	2.0/2.1	Power	
HDMI ports quantity *	3	Power source *	AC
USB 2.0 ports quantity *	1	Power consumption (standby)	0.5 W
RF ports quantity	2	Power consumption (max)	250 W
Common interface (CI)	✓	AC input voltage	120 - 240 V
Common interface Plus (CI+)	✓	TV tuner	
Network		Digital signal format system	DVB-C, DVB-S, DVB-S2, DVB-T, DVB-T2
Smart TV *	✓	Weight & dimensions	
Internet TV	✓	Width	550 mm
Ethernet LAN *	✓	Depth	296 mm
Ethernet LAN (RJ-45) ports	1	Height	120 mm
Wi-Fi *	✓	Weight	9 kg
Wi-Fi standards	802.11a, 802.11b, 802.11g, Wi-Fi 4 (802.11n), Wi-Fi 5 (802.11ac)	Package width	663 mm
Bluetooth *	✓	Package depth	403 mm
Features		Package height	289 mm
Projection type *	Front	Package weight	11.6 kg
Product type *	Ultra short throw projector		
Market positioning *	Home cinema		

Packaging content

Remote control included





6942351411149

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.