



ICY BOX IB-573SSK-12G

3 bay 3.5" SATA/SAS HDD backplane

Key features

- Host connector: 3x 7-pin SATA interface
- Supports SATA III (6 Gbit/s) and SAS III (12 Gbit/s) drives
- Full aluminium and steel backplane for 2x 5.25" bay
- Lockable drive bays
- HotSwap and Plug & Play, no capacity limit
- LED indicator for power, HDD access, fan failure, temperature alarm
- 60x60 mm cooling fan
- Alarm temperature adjustable (55° C, 60° C, 65° C)
- Supports Windows® and macOS®



Packing content

1x IB-573SSK-12G, 3x 7-pin SATA data cables, 1x Manual
8x Frame screw, 2x Key

Technical data

Model	IB-573SSK-12G
Article no.	61020
EAN code	4250078173533
Colour	Black
Material	Aluminium, steel, plastic
Space required	2x 5.25" bay
Number of HDDs	3
HDD size	3,5"
HDD interface	3x 3,5" SATA/SAS HDD
HDD capacity	Unlimited
Transfer rate	SATA up to 6 Gbit/s, SAS up to 12 Gbit/s
Interface to host computer	3x 7-pin SATA (data), 2x 15-pin SATA (power)
HotSwap	Yes
Plug & Play	Yes

Alarm	Yes
Alarm temperature	55° C, 60° C, 65° C
Settings	Fan, temperatur, buzzer
LED	Power, access and error
Cooling	60x60 mm fan
Lock	Yes
Power supply	2x 15-pin SATA power
Operating system	Windows®, macOS®
System requirements	Space required: 2x 5.25" bay Host PC with: - 2x 15-pin SATA power interface - 3x 7-pin SATA data interface Host PC with SAS technology is compatible when 3x 7-pin SATA to mini-SAS adapter cable is used (not included)



ICY BOX **IB-573SSK-12G** 3 bay 3.5" SATA/SAS HDD backplane



Stress resistant

The best materials are used in the enclosure, making this 3.5" drive solution the ideal partner for extreme loads. The backplane with its lockable bays is also ideally equipped in terms of security requirements.



Cool and silent

The active 60x60 mm fan works efficiently and adjusts its running performance to the temperatures as required, making the housing pleasantly quiet. The aluminium housing also contributes to passive convection to the surroundings.



Real time

Visual and acoustic signals indicate the current status of the hard drives and the fan. The alarm temperature for the signal can be set to three levels, 55° C, 60° C and 65° C.

Logistical data

Packing unit: 8 pcs. / carton
Total weight: 13.90 kg
Gross weight (with packing): 1.460 kg
Net weight: 1.320 kg

Dimension/carton: 520x380x280 mm
Dimension (with packing): 120x250x180 mm
Dimension of article: 215x148x86 mm
Country of origin: China