



TP-Link Deco BE22 Dual-band (2.4 GHz / 5 GHz) Wi-Fi 7 (802.11be) White 2 Internal



Brand : TP-Link

Product code: DECO BE22(2-PACK)

Product name : Deco BE22

TP-Link Deco BE22. Product colour: White, Antenna type: Internal, Product type: Mesh system. Wi-Fi band: Dual-band (2.4 GHz / 5 GHz), Top Wi-Fi standard: Wi-Fi 7 (802.11be), WLAN data transfer rate (max): 3570 Mbit/s. Parental control features: Bedtime, Custom profiles, Family online time ranking, Family time, Off time, Pause the Internet,.... AC input voltage: 100 - 240 V, AC adapter input current: 0.6 A, AC input frequency: 50/60 Hz. Certification: CE, FCC, RoHS

Design		Features	
Product type	Mesh system	DHCP client	✓
Product colour *	White	DHCP server	✓
Antenna type *	Internal	Universal Plug and Play (UPnP)	✓
Antennas quantity	4	Parental control	✓
Number of devices supported	150	Parental control features	Bedtime, Custom profiles, Family online time ranking, Family time, Off time, Pause the Internet, Professional content filter library, SafeSearch, Time rewards, Weekly/monthly reports, Youtube restriction
Reset button	✓		
Wireless LAN features			
Wi-Fi band *	Dual-band (2.4 GHz / 5 GHz)	Works with Amazon Alexa	✓
Top Wi-Fi standard *	Wi-Fi 7 (802.11be)		
WLAN data transfer rate (max) *	3570 Mbit/s		
WLAN data transfer rate (first band)	688 Mbit/s	Ports & interfaces	
WLAN data transfer rate (second band)	3882 Mbit/s	Ethernet LAN (RJ-45) ports *	2
Security algorithms	WPA-Personal, WPA2-Personal, WPA3-Personal	Power	
Point-to-point protocol over Ethernet (PPPoE)	✓	AC input voltage	100 - 240 V
Dynamic IP	✓	AC adapter input current	0.6 A
Static IP	✓	AC input frequency	50/60 Hz
Wireless Distribution System (WDS) bridge	✓	AC adapter output voltage	12 V
IGMP proxy	✓	Certificates	
IGMP snooping	✓	Certification	CE, FCC, RoHS
Tagged VLAN	✓	Operational conditions	
Dynamic DNS (DDNS)	✓	Operating temperature (T-T)	0 - 40 °C
Mobile network		Storage temperature (T-T)	-40 - 60 °C
Mobile network generation	Not supported	Operating relative humidity (H-H)	10 - 90%
Features		Storage relative humidity (H-H)	5 - 90%
Quality of Service (QoS) support	✓	Weight & dimensions	
Port forwarding	✓	Width	150 mm
		Depth	150 mm
		Height	62 mm
		Packaging content	
		Number of products included	2 pc(s)
		AC adapter included	✓
		Number of units included	2 pc(s)

Packaging content

Ethernet cable	✓
Quick installation guide	✓



1210002602808

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.