



AOC V5 CU34V5CW computer monitor 86.4 cm (34") 3440 x 1440 pixels Wide Quad HD LED Black

Brand : AOC

Product family: V5

Product code: CU34V5CW/BK

Product name : CU34V5CW

Screen size (inch) 34, Panel resolution 3440x1440, Refresh rate 100 Hz, Response time MPRT 1 ms, Panel type VA, USB-C connectivity USB-C 3.2 x 1 (DP alt mode, upstream, power delivery up to 65 W), HDMI HDMI 2.0 x 1, Display Port DisplayPort 1.2 x 1, D-SUB (VGA) 0x, DVI 0x, Sync technology (VRR) Freesync

AOC V5 CU34V5CW computer monitor 86.4 cm (34") 3440 x 1440 pixels Wide Quad HD LED Black:

34" VA WQHD model for complex multitasking, with USB-C, MultiView and Windows Hello integrated webcam

The AOC CU34V5CW is a three-side frameless curved monitor equipped with a 34" VA panel with QHD UltraWide 21:9 resolution for an impressive and immersive viewing experience, ready to support any complex work with Picture by Picture MultiView. It offers a wide array of connectivity options thanks USB-C with Power Delivery up to 65W, 4 USB ports & HDMI. Log in easily and securely with Windows Hello integrated webcam.



Display		Ports & interfaces	
Display diagonal *	86.4 cm (34")	HDMI *	✓
Display resolution *	3440 x 1440 pixels	HDMI ports quantity	1
HD type *	Wide Quad HD	HDMI version	2.0
Native aspect ratio *	21:9	DisplayPorts quantity	1
Display technology *	LED	DisplayPort version	1.2
Panel type *	VA	Headphone out *	✓
LED backlight	✓	Headphone outputs	1
Backlight type	W-LED	Headphone connectivity	3.5 mm
Touchscreen *	✗	Built-in KVM switch	✗
Display brightness (typical)	300 cd/m²	AC (power) in	✓
Response time *	4 ms	Mobile High-Definition Link (MHL)	✗
Response time measurement type	GTG (Gray to Gray)	Network	
Response time (MPRT)	1 ms	Ethernet LAN	✗
Anti-glare screen	✓	Ergonomics	
Screen shape *	Curved	VESA mounting *	✓
Screen curvature rating	1500R	Panel mounting interface	100 x 100 mm
Contrast ratio (typical) *	3000:1	Wall mountable	✓
Contrast ratio (dynamic)	20000000:1	Cable lock slot *	✓
Maximum refresh rate *	100 Hz	Cable lock slot type	Kensington
Viewing angle, horizontal	178°	Height adjustment *	✓
Viewing angle, vertical	178°	Adjustable height (max)	13 cm
Display number of colours *	16.7 million colours	Pivot	✗
Pixel pitch	0.23175 x 0.23175 mm	Swivelling	✓
Pixel density	110 ppi	Tilt adjustment	✓
Display diagonal (metric)	86.4 cm	Tilt angle range	3 - 21°
Surface hardness	6H	On Screen Display (OSD)	✓
Performance			
NVIDIA G-SYNC *	✗		

Performance		Ergonomics	
AMD FreeSync *	✓	On Screen Display (OSD) languages	Simplified Chinese, Traditional Chinese, Czech, Dutch, English, Finnish, French, German, Italian, Japanese, Korean, Croatian, Polish, Portuguese, Russian, Spanish, Swedish, Turkish, Ukrainian
AMD FreeSync type	FreeSync		
Fast charging	✓		
Flicker-free technology	✓	Number of OSD languages	19
Low Blue Light technology	✓	LED indicators	✓
Multimedia		Power	
Number of speakers	2	Energy efficiency class (SDR) *	G
RMS rated power	10 W	Energy efficiency class (HDR) *	G
Built-in speaker(s) *	✓	Energy consumption (SDR) per 1000 hours *	34 kWh
Megapixel (approx.)	2 MP	Energy consumption (HDR) per 1000 hours *	35 kWh
Built-in microphone	✗	Power consumption (standby) *	0.5 W
Built-in camera *	✓	Power consumption (off)	0.3 W
Design		AC input voltage	100 - 240 V
Market positioning *	Home	AC input frequency	50/60 Hz
Product colour *	Black	Power supply type	Internal
Frameless design	✓	Energy efficiency scale	A to G
Front bezel colour	Black	Packaging data	
Detachable stand	✓	USB cable length	1.8 m
Feet colour	Black	Packaging content	
Ports & interfaces		Stand included	✓
Built-in USB hub *	✓	Cables included	AC, HDMI, USB Type-C
USB hub version	3.2 Gen 1 (3.1 Gen 1)	HDMI cable length	1.5 m
USB upstream port type	USB Type-C	Other features	
Number of upstream ports	1	Picture-by-Picture (PbP)	✓
Number of USB Type-C upstream ports quantity	1	Exterior finish type	Matt
USB Type-A downstream ports quantity	4	Bezel thickness type	Frameless
USB Type-C DisplayPort Alternate Mode	✓	Warranty period	3 year(s)
USB Power Delivery (USB PD)	✓	Compliance certificates	CE
USB Power Delivery up to	65 W	Mean time between failures (MTBF)	50000 h
DVI port	✗	Light effects	✗
		Supplied AC adapter type	False
		Certification	CB,EAC



4038986110273

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.