

GIGABYTE P650G PCIE 5.1 Power Supply - PCIe 5.1, 80 PLUS Silver, 120mm Fan, ATX 3.1 compatible, EU Plug

Brand : GIGABYTE

Product code: GP-P650G PG5 EU

Product name : P650G PCIE 5.1 Power Supply - PCIe 5.1, 80 PLUS Silver, 120mm Fan, ATX 3.1 compatible, EU Plug

- ATX 3.1 and PCIe Gen 5.1 ready
- 80 PLUS Gold certified
- Main Japanese capacitors
- 120mm Silent Hydraulic Bearing (HYB) Fan
- Powerful single +12V rail
- OVP/OPP/SCP/UVF/OCF/OTP protection
- Compact design

P650G PCIE 5.1 Power Supply - PCIe 5.1, 80 PLUS Silver, 120mm Fan, ATX 3.1 compatible, EU Plug

GIGABYTE P650G PCIE 5.1 Power Supply - PCIe 5.1, 80 PLUS Silver, 120mm Fan, ATX 3.1 compatible, EU Plug:

Ensure reliable and efficient power delivery with GIGABYTE power supplies. Designed for peak performance and durability, our PSUs offer stable and consistent energy to power your high-performance systems. With advanced protections and high-quality components, GIGABYTE power supplies provide the confidence you need for seamless, uninterrupted computing experiences.



Power		Ports & interfaces	
Total power *	650 W	PCI Express power cable length	50 cm
AC input voltage *	100 - 240 V	CPU P4 connector (4-pin)	1
AC input frequency	50/60 Hz	CPU power connector (4+4 pin)	✓
Input current	10 - 6 A	CPU power cable length	60 cm
Maximum input current (@110V)	10 A	ATX power connector (20+4 pin)	✓
Maximum input current (@220V)	6 A	Floppy disk drive connector	✓
Power Factor Correction (PFC) type	Active	Cabling type	Non-Modular
Combined power (+3.3V)	90 W	Performance	
Combined power (+12V)	650 W	80 PLUS certification *	80 PLUS Gold
Combined power (+5V)	650 W	Purpose *	PC
Combined power (-12V)	3.6 W	Power supply unit (PSU) form factor *	ATX
Combined power (+5Vsb)	15 W	ATX version	3.1
Max output current (+3.3V)	18 A	Bearing technology	HYB
Max output current (+12V)	54.2 A	Mean time between failures (MTBF)	100000 h
Max output current (+5V)	18 A	Design	
Max output current (-12V)	0.3 A	Product colour	Black
Max output current (+5Vsb)	18 A	Cooling type	Active
Power Good signal delay range	100 - 150 ms	Fan diameter	12 cm
Power protection features	Over power, Overcharge, Short circuit, Under voltage	Number of fans	1 fan(s)
Ports & interfaces		Fan location	Top
Motherboard power connector *	20+4 pin ATX	On/off switch	✓
Motherboard power cable length	60 cm	Weight & dimensions	
Number of SATA power connectors	6	Width	140 mm
SATA power cable length	120,500 mm	Depth	150 mm
Peripheral (Molex) power connectors (4-pin) *	3	Height	86 mm
Peripheral (Molex) power cable length	150 mm	Weight	1.76 kg

Ports & interfaces		Packaging data	
PCI Express power connectors (6+2 pin)		Package width	260 mm
		Package depth	110 mm
		Package height	180 mm
		Package weight	1.92 kg
		Package type	Box
		Logistics data	
		Warranty period	5 year(s)



4719331556785

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.