



## BenQ MX560 Standard throw projector 4000 ANSI lumens DLP XGA (1024x768) White

**Brand :** BenQ

**Product code:** 9H.JNE77.13E

**Product name :** MX560



- 4000 ANSI Lumen High brightness and 20,000:1 High Contrast  
- Exclusive Data Review Mode Showcases Text and Charts in Detail  
- SmartEco Mode Saves Lamp Power Up To 70%  
DLP, 4000 Lumens, 20000:1, 4:3, 1024 x 768, 34 /29 dBA, Composite Video in, 2 x HDMI, VGA, RS-232, USB Type-A, USB Mini-B, 296 x 120 x 221 mm, 2.3kg  
BenQ MX560. Projector brightness: 4000 ANSI lumens, Projection technology: DLP, Projector native resolution: XGA (1024x768). Light source type: Lamp, Service life of light source: 6000 h, Service life of light source (economic mode): 10000 h. Zoom ratio: 1.1:1, Throw ratio: 1.96 - 2.15, Offset: 110%. Analog signal format system: NTSC, PAL, SECAM, Supported graphics resolutions: 640 x 480 (VGA), 1024 x 768 (XGA), 1920 x 1200 (WUXGA), Supported video modes: 480i, 480p, 576i, 576p, 720p, 1080i, 1080p. Serial interface type: RS-232, HDMI connector type: Full-size



| Projector                                    |                                                        | Storage                           |                                                                                                                                                                                                                                                                                 |
|----------------------------------------------|--------------------------------------------------------|-----------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Screen size compatibility *                  | 1524 - 3810 mm (60 - 150")                             | Card reader integrated *          | ×                                                                                                                                                                                                                                                                               |
| Projector brightness *                       | 4000 ANSI lumens                                       | <b>Features</b>                   |                                                                                                                                                                                                                                                                                 |
| Projection technology *                      | DLP                                                    | Noise level (economic mode)       | 29 dB                                                                                                                                                                                                                                                                           |
| Projector native resolution *                | XGA (1024x768)                                         | On Screen Display (OSD)           | ✓                                                                                                                                                                                                                                                                               |
| Contrast ratio (typical) *                   | 20000:1                                                | On Screen Display (OSD) languages | Arabic, Bulgarian, Simplified Chinese, Traditional Chinese, Croatian, Czech, Danish, German, Dutch, English, Spanish, Finnish, French, Greek, Hindi, Hungarian, Italian, Japanese, Korean, Norwegian, Polish, Portuguese, Romanian, Russian, Swedish, Thai, Turkish, Vietnamese |
| Native aspect ratio *                        | 4:3                                                    |                                   |                                                                                                                                                                                                                                                                                 |
| Horizontal scan range                        | 15 - 102 kHz                                           |                                   |                                                                                                                                                                                                                                                                                 |
| Vertical scan range                          | 23 - 120 Hz                                            |                                   |                                                                                                                                                                                                                                                                                 |
| Keystone correction, vertical                | -40 - 40°                                              | Number of OSD languages           | 30                                                                                                                                                                                                                                                                              |
| Matrix size                                  | 1.4 cm (0.55")                                         | Noise level *                     | 34 dB                                                                                                                                                                                                                                                                           |
| Light source                                 |                                                        | Air filter                        | ✓                                                                                                                                                                                                                                                                               |
| Light source type *                          | Lamp                                                   | <b>Multimedia</b>                 |                                                                                                                                                                                                                                                                                 |
| Service life of light source *               | 6000 h                                                 | Built-in speaker(s) *             | ✓                                                                                                                                                                                                                                                                               |
| Service life of light source (economic mode) | 10000 h                                                | RMS rated power                   | 10 W                                                                                                                                                                                                                                                                            |
| Lamps quantity                               | 1 lamp(s)                                              | <b>Design</b>                     |                                                                                                                                                                                                                                                                                 |
| Lens system                                  |                                                        | Market positioning *              | Business                                                                                                                                                                                                                                                                        |
| Zoom capability                              | ✓                                                      | Product type *                    | Standard throw projector                                                                                                                                                                                                                                                        |
| Zoom ratio                                   | 1.1:1                                                  | Product colour *                  | White                                                                                                                                                                                                                                                                           |
| Throw ratio                                  | 1.96 - 2.15                                            | Placement                         | Ceiling, Floor                                                                                                                                                                                                                                                                  |
| Offset                                       | 110%                                                   | Cable lock slot                   | ✓                                                                                                                                                                                                                                                                               |
| Video                                        |                                                        | Cable lock slot type              | Kensington                                                                                                                                                                                                                                                                      |
| Analog signal format system *                | NTSC, PAL, SECAM                                       | <b>Display</b>                    |                                                                                                                                                                                                                                                                                 |
| Supported graphics resolutions               | 640 x 480 (VGA), 1024 x 768 (XGA), 1920 x 1200 (WUXGA) | Built-in display *                | ×                                                                                                                                                                                                                                                                               |
| Supported video modes                        | 480i, 480p, 576i, 576p, 720p, 1080i, 1080p             |                                   |                                                                                                                                                                                                                                                                                 |

| Ports & interfaces           |           | Power                            |             |
|------------------------------|-----------|----------------------------------|-------------|
| HDMI connector type          | Full-size | Power source *                   | AC          |
| S-Video inputs quantity      | 1         | Power consumption (typical) *    | 260 W       |
| USB 2.0 ports quantity       | 1         | Power consumption (standby) *    | 0.5 W       |
| Mini-USB 2.0 ports quantity  | 1         | Power consumption (max)          | 280 W       |
| Microphone in                | ✓         | Power consumption (economy mode) | 215 W       |
| Serial interface type *      | RS-232    | AC input voltage                 | 100 - 240 V |
| PC in (D-Sub)                | ✓         | AC input frequency               | 50 - 60 Hz  |
| VGA (D-Sub) ports quantity * | 2         | Operational conditions           |             |
| HDMI ports quantity *        | 2         | Operating temperature (T-T)      | 0 - 40 °C   |
| Composite video in *         | 1         | Weight & dimensions              |             |
| DVI port *                   | ✗         | Width                            | 296 mm      |
| AC (power) in                | ✓         | Depth                            | 221 mm      |
| Network                      |           | Height                           | 120 mm      |
| Smart TV *                   | ✗         | Weight *                         | 2.3 kg      |
| Ethernet LAN *               | ✗         | Packaging content                |             |
| Wi-Fi *                      | ✗         | Remote control included *        | ✓           |
|                              |           | Remote control type              | IR          |
|                              |           | Batteries included               | ✓           |
|                              |           | Cables included                  | AC, VGA     |
|                              |           | Logistics data                   |             |
|                              |           | Quantity per pack                | 1 pc(s)     |
|                              |           | Harmonized System (HS) code      | 85286200    |



4718755084218

### Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.